

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
1	NEUROSURGERY EQUIPMENT					
1.1	Electric Bur of Craniotomy and Trepanation			1	Unit	
		Operational	: Touch Screen			
		Display	: approx.6.5 inch LCD Screen			
		Motor Connection	: 2			
		Foot Control	: Single foot control or multi foot control			
			(1 pedal with 1 or 3 buttons, speed control :variable)			
		Weight	: approx. 6.9 kg			
		<i>Dimension</i>	: W278 x D268 x H160 (mm) approx			
		Power Supply	: AC 120V/230V, 50/60 Hz			
		Speed Control	: Yes			
		Reverse Rotation Control	: Yes			
		Irrigation Pump	: Yes			
		Axel Adjustment	: Myes (min 10% - max 100%)			
		Brake Adjustment	: yes (min 10% - max 100%)			
		Torque Adjustment	: yes (min 10% - max 100%)			
		Memory Function	: yes			
		Oscillating Adjustment	: 1-5 times, available for Wire PIN Driver			
		Slim motor handpieces				
		<i>Product Line Up</i>	: 2			
		RPM	: 1.000 s/d 80.000			
		Weight	: approx100 gr			
		Autoclavable	: yes			
		Slim handpieces	: 80.000 RPM, 23 kinds handpieces			
		Super slim handpieces	: 20.000 RPM			
		Standard angled handpieces	: 80.000 RPM			
		Standard straight handpieces	: 80.000 RPM			
		Perforator handpieces (Hudson Chuck)	: 1.250 RPM			
		Craniotome handpieces	: 80.000 RPM for diameter 3.17 mm bur			
		Drill trephination handpieces	: 80.000 RPM for diameter 2.35 mm twist drill			
		Micro bone saw handpieces				
		Reciprocating saw handpieces	: 20.000 RPM			
		Sagital saw handpieces	: 20.000 RPM			
		Oscillating saw handpieces	: 20.000 RPM			
		Wire PIN Driver Handpieces feature				

NO.	Item	Purchaser's Specifications	Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		Wire and PIN Collet	: 1.200 RPM rotation mode : Forward, Reverse, Oscillating		
		Attachment : Drill attachment	: Jacobs keyed drill chuck, AO drill chuck, keyless drill chuck		
		Attachment : Reamer attachment	: 300 RPM : Hudson modified trinkle Reamer, AO Reamer		
		Attachment : Saw attachment	: 12.000 RPM : Reciprocating saw, Sagital Saw		
		Control Unit			
		Primado 2 Control Unit for 230V		1	pc
		Configuration For Craniotome and High Speed Drill			
		Primado 2 Slim Motor		1	pc
		RPM	: 1.000 s/d 80.000		
		Weight	: 100 gr		
		Autoclavable	: yes		
		Conect to 23 kinds handpieces			
		Primado 2 Multi Foot Control		1	pc
		1 pedal with 3 butons			
		speed control	: variable		
		JP code	: JP x 8		
		Craniotome Handpiece and Bur			
		Craniotome handpieces 80.000 RPM with Duraguard Medium		2	pcs
		Craniotome Burr, medium, 1.6 mm		15	pcs
		Perforator			
		Perforator handpieces speed	: 1.250 RPM	1	pc
		Perforator handpieces 200 (include Perforator Drill)		1	pc
		Attachment And Burs			
		Standard Straight Handpieces 200 Extra Short		1	pc
		Standard Angle Handpieces 200 Extra Short		1	pc
		Irrigation Nozzle for P200-2SES and P200 - 2 AES		2	pcs
		Standard Angle Handpieces 200 Medium		1	pc
		Irrigation Nozzle for P200-2SES and P200 - 2 AES		1	pc
		Irrigation Nozzle for P200-2AM		1	pc
		Irrigation Tube (@ 1 box = 10 pcs)		3	pcs
		Round fluted bur, extra short, 1.0 mm		3	pcs
		Round fluted bur, extra short, 3.0 mm		3	pcs
		Round fluted bur, extra short, 4.0 mm		3	pcs

NO.	Item	Purchaser's Specifications	Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		Round fluted bur, extra short, 7.0 mm	3	pcs	
		Diamond bur, extra short, 2.0 mm	3	pcs	
		Diamond bur, extra short, 3.0 mm	3	pcs	
		Diamond bur, extra short, 4.0 mm	3	pcs	
		Diamond bur, extra short, 7.0 mm	3	pcs	
		Coarse diamond bur, extra short, 2.0 mm	3	pcs	
		Coarse diamond bur, extra short, 3.0 mm	3	pcs	
		Round fluted bur, medium, 2.0 mm	3	pcs	
		Round fluted bur, medium, 3.0 mm	3	pcs	
		Round fluted bur, medium, 4.0 mm	3	pcs	
		Round fluted bur, medium, 5.0 mm	3	pcs	
		Diamond dust bur, medium, 2.0 mm	3	pcs	
		Diamond dust bur, medium, 3.0 mm	3	pcs	
		Diamond dust bur, medium, 4.0 mm	3	pcs	
		Diamond dust bur, medium, 5.0 mm	3	pcs	
		Tray and Trolley			
		Sterilization Cassette / H70	1	pc	
		Sterilization Metal Lid	1	pc	
		Silicone Mat	1	pc	
		Mobile Trolley	1	pc	
1.2	Basic Neurosurgery Instrument Set		1	Set	
		Scalpel handle No. 3, 12.5 cm	1	pc	
		Scalpel handle No.4	1	pc	
		Dressing forceps, Modell USA 14.5 cm	2	pcs	
		Dressing forceps, Modell USA, 18 cm	1	pc	
		Debakey atrauma forceps, 1.5 mm tip 20 cm	2	pcs	
		Tissue forceps, Modell USA, 14.5 cm	2	pcs	
		Potts Smiths tissue forceps, delicate, 21 cm	2	pcs	
		Scissors, straight, SH/BL.14.5 cm	1	pc	
		Metzenbaum scissors TC, curved, 14.5 cm	1	pc	
		Toenis adson TC tonsil scissors, curved, 17.5 cm	1	pc	
		Debakey scissors 60 of angle, 16 cm	1	pc	
		Mayo hegar TC, needle holder, 16 cm	2	pcs	

NO.	Item	Purchaser's Specifications	Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		Serot TC needle holder, 18 cm	2	pcs	
		Pean haemostatic forceps, 16 cm	1	pc	
		Halstead mosquito haemostatic fcps, str 12.5 cm	12	pcs	
		Halstead mosquito haemostatic fcps, cvd 12.5 cm	8	pcs	
		Halstead mosquito haemostatic fcps, str 14cm	4	pcs	
		Halstead mosquito haemostatic fcps, cvd 14cm	4	pcs	
		Backhaus towel forceps, 11 cm	10	pcs	
		Volkman retractor, semi sharp, 6 prongs, 22.5 cm	2	pcs	
		Cushing nerve retractor, 19 cm	1	pc	
		Beyer bone rongeur 18 cm	1	pc	
		Round bowl 147 x 65 mm	1	pc	
		Bulldog clamps dietrich 4.9 cm	2	pcs	
		Bulldog clamps dietrich 5.3 cm	2	pcs	
		Bulldog clamps dietrich 4.3 cm	2	pcs	
		Bulldog clamps dietrich 4.5 cm	2	pcs	
		Clip applying fcps,str. 14 cm	1	pc	
		Vessel clips,str.jaw 4x0.75mm, locking pressure 125g	2	pcs	
		Vessel clips,str.jaw 6x1mm, locking pressure 100g	2	pcs	
		Vessel clips,str.jaw 8x2mm, locking pressure 85g	2	pcs	
		Weitlaner retractor blunt, 13 cm	1	pc	
		Love nerve retractor, 21 cm	1	pc	
		Hone nerve retractor, 22 cm	2	pcs	
		Instrument tray perforated, 48 x 27 x 5 cm	1	pc	
2	DIGESTIVE ENDOSCOPY / SURGERY EQUIPMENT				
2.1	2D Monitor 26 " HD		1	Unit	
		26" FULL HD Monitor, color			
		systems PAL/NTSC, max. screen			
		resolution 1920 x 1080, image			
		format 16:9, video inputs: DVI,			
		3GSDI,			
		VGA, S-Video, Composite,			
		video outputs: DVI, 3G-SDI,			
		Composite, power supply 100 - 240			
		VAC, 50/60 Hz, 5 V DC output (1			
		A), wall-mounted with VESA 100			
		adaption, including: External 24			
		VDC Power Supply Mains Cord			
2.2	Image I S 2D Rigid Endoscope Type 1		1	Unit	

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		TC200 (IMAGE 1 CONNECT)	: IMAGE 1 CONNECT, connect module, for use with up to 3 link modules,	1	pc	
			resolution 1920 x 1080 pixels, with integrated SCB and digital Image Processing Module,			
			power supply 100 - 120 VAC, 50/60 Hz; 200 - 240 VAC, 50/60 Hz consisting of: 400 A			
			Mains Cord, length approx 300 cm 20040089 DVI Signal Cable, length approx 300 cm 20090170 SCB Connecting Cable, length 100 cm 20040282			
			USB Flash Drive, 32 GB			
		TC300 (IMAGE 1 H3-LINK)	: IMAGE 1 H3-LINK, link module, for use with IMAGE 1 FULL HD threechip camera heads	1	pc	
			power supply 100 - 120 VAC/200 - 240 VAC, 50/60 Hz,			
			for use with IMAGE 1 CONNECT TC 200EN,			
			consisting of: 400 A Mains Cord, length approx 300 cm TC 011 Link Cable, length approx 20 cm			
		TH102 (IMAGE1 H3-Z FISPIES)	: IMAGE 1 H3-Z FI SPIES Three-Chip FULL HD Camera Head, SPIES compatible	1	pc	
			for perfusion diagnosis of tissues and organs with indocyanine green (ICG) in conjunction with light source DLIGHT P			
			progressive scan			
			with integrated Parfocal Zoom Lens			
			focal length f = 15 - 31 mm (2x)			
			with 2 freely programmable camera head buttons			
			for use with IMAGE1 SPIES and IMAGE 1 HUB HD/IMAGE1 HD			
2.3	Xenon 300 D-Light P SCB			1	Unit	
		Cold Light Fountain DLIGHT P SCB	: Cold Light Fountain D-LIGHT PSCB, with integrated SCB	1	pc	
			high-performance light unit for perfusion assessment			
			autofluorescence and standard endoscopic diagnosis			

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
			including a 300 Watt Xenon bulb and KARL STORZ light cable connection			
			power supply 100 - 125/220 - 240 VAC, 50/60 Hz including: 400 A			
			Mains Cord 20090170 SCB Connecting Cable 20014130 One-Pedal Footswitch, one-stage, for switch function 96240726 Democard Fluorescence I			
2.4	HF Unit			1	Unit	
		AUTOCON® II 400 High-End Set	: AUTOCON® III 400 High-End	1	pc	
			power supply 220 - 240 VAC, 50/60 Hz			
			including mains cord			
			HF connecting sockets unipolar: 2x3-pin US type 5 mm connector KARL STORZ/Erbe VIO 2x 4 mm connector (via footswitch) BOVIE (via footswitch) bipolar: 2x 2-pin US type (28.58) 3x KARL STORZ/Erbe VIO Neutral electrode 2-pol.			
			Can be integrated into OR1 with control system			
			System requirements: SCB-R-UI Software Release 20090001-46 or higher			
		Neutral Electrode	: Neutral Electrode made with 2 rubber straps for fastening conductive silicone	1	pc	
			AUTOCON II 400 (type 111, 115) A= 500 cm² surface area.			
			Connecting cord is required			
		Two-pedal footswitch for HF Generators	: Two-Pedal Footswitch with button for switchover function, for use with HF generators	1	pc	
		One-pedal Hffootswitch	: One-Pedal Footswitch, with button for switchover function, for use with HF generators	1	pc	
		Connecting cord neutral electrode	: Connecting cord neutral electrode	1	pc	
		(Bottle Cap, 1.5 and 5 l	: Bottle Cap, 1.5 and 5 l	1	pc	
2.5	Insufflator Premium			1	Unit	

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		Silicone Tubing Set, CO2 ENDOFLATOR®	: Silicone Tubing Set, sterilizable, for use with Electronic Endoflator 26430520	1	pc	
		CO2 High Pressure Tube, 102 cm	: High Pressure Hose, american connection / German connection (CO2), length 102 cm	1	pc	
		CO2 Bottle, empty, German connection	: CO2-Bottle, empty, with German connection	1	pc	
		THERMOFLATOR®SCB, Set	: THERMOFLATOR® SCB, with integrated SCB module, power supply 100 - 240 VAC, 50/60 Hz consisting of: 26432020-1 THERMOFLATOR® with Heating Element, autoclavable 20400043 Silicone Tubing Set, sterilizable 20400030 Universal Wrench 20090170 SCB Connecting Cable, length 100 cm 031122-10 Gas Filter, sterile, for single use, package of 10	1	pc	
2.6	Basic Set Laparoscopy Cholecystectomy & Appendectomy			1	Unit	
		Trocar, size 11 mm (30103MP)	: Trocar, size 11 mm, color code: green, consisting of: 30103 P Trocar only, with pyramidal tip 30103 H2 Cannula without valve, with insufflation stop-cock, length 10.5 cm 30103 M1 Multifunctional Valve	2	pcs	
		Trocar, size 6 mm (30160MP)	: Trocar, size 6 mm, consisting of: 30160 P Trocar only, with pyramidal tip 30160 H2 Cannula without valve with insufflation stop-cock, length 10.5 cm 30160 M1 Multifunctional Valve	3	pcs	
		Cleaning Brush, 7 mm, 35 cm	: Cleaning Brush, length 35 cm, O.D. 7 mm	1	pc	
		Cleaning Brush, 50 cm, 11 mm	: Cleaning Brush, length: 50 cm, O.D. 11 mm	1	pc	
		Cleaning Brush, 11 mm, 35 cm	: Cleaning Brush, length 35 cm, O.D. 11 mm	1	pc	
		Instrument Oil, 50 ml	: Oil for Instruments, Bottle of 50 ml	1	pc	
		HOPKINS® Telescope 30°, 5 mm	: HOPKINS® Forward-Oblique Telescope 30°, diameter 5 mm, length 29 cm, autoclavable, fiber optic transmission light incorporated, color code: red	1	pc	
		VERESS Pneumoperitoneum Needle, 13 cm	: VERESS Pneumoperitoneum Needle, with spring-loaded blunt inner cannula, LUER-Lock, autoclavable, diameter 2.1 mm, length 13 cm	1	pc	

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		Handle with Two-Way Stop-cock	: Handle with Two-way Stop-cock for suction and irrigation, autoclavable, for use with suction and irrigation tubes size 5 mm	1	pc	
		Disinfection System, 740 x 220 x 132	: Disinfection System, for use with fiberscopes, external dimensions (w x d x h): 740 x 220 x 132 mm consisting of: 1. Soak Basin 2. Perforated Storage Tray 3. Lid	1	pc	
		Cleaning agent, tube 5 gr	: Cleaning agent for distal and proximal lenses and fiber optic surfaces of endoscopes, tube 5 gr.	1	pc	
		Suction a. Irrig. Cannula, L. 36cm	: Special-lubricant for stop-cocks	1	pc	
		Coagulating and Dissecting Electrode, L Hook	: Suction and Irrigation Cannula with lateral holes, size 5 mm, length 36 cm, for use with suction and irrigation handles	1	pc	
		Coagulating and Dissecting Electrode, Spatula	: Coagulating and Dissecting Electrode, L-shaped, with connector pin for unipolar coagulation, size 5 mm, working length 36 cm	1	pc	
			: Coagulating and Dissecting Electrode, spatula-shaped, blunt with connector pin for unipolar coagulation, size 5 mm, working length 36 cm	1	pc	
		Knot Tier, 5 mm, 36cm A	: KÖCKERLING Knot Tier, size 5mm, working length 36 cm, for extracorporeal knotting	1	pc	
		Reduction Sleeve, 5/3mm	: Reduction Sleeve, reusable, instrument size 3 mm, trocar cannula size 6 mm, color code: black	1	pc	
		Reduction Sleeve, 11/5 mm	: Reduction Sleeve, 11/5 mm	1	pc	
		Reducer, 11/5 mm	: Reducer, 11/5 mm	1	pc	
		Bipolar High Frequency Cord, length 300 cm	: Bipolar High Frequency Cord, length 300 cm, for AUTOCON® II 400 SCB system (111, 113, 115, 122, 125), AUTOCON® II 200, AUTOCON® II 80, Coagulator 26021 B/C/D, 860021 B/C/D, 27810 B/C/D, 28810 B/C/D, AUTOCON® series (50, 200, 350), Erbe-Coagulator, T and ICC series, length 300 cm	1	pc	

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		Unipolar High Frequency Cord, 300 cm	: Unipolar High Frequency Cord, with 5 mm plug, length approx 300 cm, for use with AUTOCON® II 400 SCB system (111, 115, 122, 125), AUTOCON® II 200, AUTOCON® II 80, KARL STORZ AUTOCON® system (50, 200, 350) and Erbetype ICC	1	pc	
		CLICKLINE Plastic Handle	: Plastic handle, without ratchet with connector pin for unipolar coagulation	5	pcs	
		Metal Outer Sheath, insulated, 36 cm	: Insulated Metal Outer Tube, with LUER-Lock connector, size 5 mm, length 36 cm	8	pcs	
		CLICKLINE Forceps Insert with especially fine atraumatic serration	: CLICKLINE Forceps Insert, Grasping Forceps, with especially fine atraumatic, serration, fenestrated, single action jaws, size 5 mm, length 36 cm	1	pc	
		CLICKLINE Forceps Insert Grasping Forceps heavy	: CLICKLINE Forceps Insert, REDDICK-OLSEN Dissecting and Grasping Forceps heavy, double action jaws, size 5 mm, length 36 cm	1	pc	
		CLICKLINE Forceps Insert double action jaws, size 5 mm	: CLICKLINE Forceps Insert, KELLY Dissecting and Grasping Forceps, double action jaws, size 5 mm, length 36 cm	1	pc	
		CLICKLINE Forceps Insert double action jaws	: CLICKLINE Forceps Insert, Dissecting and Grasping Forceps, atraumatic, double action jaws, size 5 mm, length 36 cm	1	pc	
		CLICKLINE Scissors use with trocars size 6 mm	: CLICKLINE Scissors Insert, for METZENBAUM scissors, double action jaws, curved, size 5 mm, length 36 cm, for use with trocars size 6 mm	1	pc	
		CLICKLINE Scissors Insert Hook Scissors	: CLICKLINE Scissors Insert, Hook Scissors, single action jaws, size 5 mm, length 36 cm	1	pc	
		CLICKLINE Forceps Insert "Tiger-Jaws", 2x 4 teeth, single	: CLICKLINE Forceps Insert, MANHES Grasping Forceps, "Tiger-Jaws", 2 x 4 teeth, single action jaws, size 5 mm, length 36 cm	1	pc	
		CLICKLINE Forceps Insert size 5 mm, length 36 cm	: CLICKLINE Forceps Insert, Dissecting and Grasping, right angled, double action jaws, size 5 mm, length 36 cm	1	pc	

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		CLICKLINE Plastic Handle with larger contact area	: CLICKLINE Plastic Handle, with MANHES style ratchet, with larger contact area at the finger ring, with connector pin for unipolar coagulation	3	pcs	
		Metal Outer Sheath, insulated, 43 cm	: Insulated Metal Outer Tube, with LUER-Lock connector size 5 mm, length 43 cm	1	pc	
		CLICKLINE Forceps Insert Bowel Grasper, double action jaws	: CLICKLINE Forceps Insert, Bowel Grasper, fenestrated, double action jaws, length of jaws 18 mm, size 5 mm, length 43 cm	1	pc	
		CLICKLINE Metal Handle without ratchet	: Metal Handle , without ratchet	1	pc	
		Outer Sheath, insulated	: Outer Tube, with LUER-Lock, connector, size 10 mm, length 36 cm	1	pc	
		CLICKLINE Forceps Insert, long	: Forceps Insert, long	1	pc	
		RoBi® KELLY Forceps Insert	: RoBi® KELLY Forceps Insert, CLERMONT-FERRAND model, especially suitable for dissection, double action jaws, size 5 mm, length 36 cm, color code: light blue	1	pc	
		RoBi® Metal Outer Sheath length 36 cm	: RoBi® Metal Outer Sheath, insulated, with LUER-Lock connector for cleaning, size 5 mm, length 36 cm	1	pc	
		Fluid Light Cable, 250cm, ø5mm	: Fluid Light Cable, diameter 5 mm, length 250 cm	1	pc	
		HOPKINS® II Telescope 0°, ICG, Ø 10mm	: HOPKINS® Straight Forward Telescope 0°, enlarged view, diameter 10 mm, length 31 cm, autoclavable, for indocyanine green (ICG) and autofluorescence (AF), fiber optic light transmission incorporated, for use with Fluid Light Cable 495 FQ/FR and Cold Light Fountain D-LIGHT P SCB 20133701-1, color code: green	1	pc	
2.7	Hernia & Appendectomy Instrument Set			1	Set	
		MAIER FORCEPS W/RCHT CVD260MM		2	pc	
		BACKHAUS TOWEL CLAMP 110MM		4	pc	
		TOWEL CLAMP FOR PAPER CLOTHS 115MM		2	pc	
		SCALPEL HANDLE #4 135MM		2	pc	
		SCALPEL HANDLE #3 125MM		1	pc	

NO.	Item	Purchaser's Specifications	Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		TC METZENBAUM SCISSORS DEL CVD 180MM	1	pc	
		TC SUTURE WAVECUT SCISSORS CVD 180MM	1	pc	
		TC MAYO-LEXER SCISSORS CVD 165MM	1	pc	
		SURGICAL SCISSORS STR S/B145MM	1	pc	
		TISSUE FORCEPS SERR 145MM	1	pc	
		TISSUE FORCEPS STR 1X2 145MM	2	pc	
		DEBAKEY ATR.FCPS 2.0MM STR150MM	2	pc	
		KOCHER FORCEPS STR 1X2 140MM	6	pc	
		PEAN FORCEPS STR 140MM	6	pc	
		HALSTED-MOSQUITO FORCEPS DEL CVD125MM	6	pc	
		KOCHER-OCHSNER FORCEPS STR 1X2 200MM	2	pc	
		MAIER FORCEPS W/RCHT STR 260MM	2	pc	
		MIKULICZ PERITONEUM FORCEPS CVD.200MM	4	pc	
		OVERHOLT FORCEPS # 1 CVD210MM	2	pc	
		OVERHOLT FORCEPS # 2 CVD 220MM	2	pc	
		DESCHAMPS NDLF/RT- HNDBLTLNG-HK215MM	1	pc	
		KOENIG GUIDE PROBE 5MM195MM	1	pc	
		TC CRILE-WOOD NDL HLDRSTRSERR 145MM	1	pc	
		TC MAYO-HEGAR NDL HOLDERHVYSERR205MM	2	pc	
		TC DEBAKEY NDL HOLDER DEL SERR 180MM	1	pc	
		ROUX RETRACTOR 3/SET 165MM	1	pc	
		LANGENBECK RETRACTOR 33X14MM 210MM	2	pc	
		INTERIOR BOX F/BL930	1	pc	
		LABORATORY DISH 0.16 L	1	pc	
		LABORATORY DISH 0.3 L	1	pc	
		KIDNEY TRAY STAINLESS STEEL 250MM	1	pc	
		REDON SPIKE CH.12 SLIG.CVD.TRIANG.TIP	1	pc	
		REDON SPIKE CH.14 SLIG.CVD.TRIANG.TIP	1	pc	
		STERILIT I OIL SPRAY	1	pc	

NO.	Item	Purchaser's Specifications	Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		BASKET WIDE PERFORATION 485X253X76MM	1	pc	
		BOTTOM FOR 1/1 CONTAINER HEIGHT:135MM	1	pc	
		BOTTOM MOD.CONTAINER PERF.589X363X167MM	1	pc	
3	PLASTIC SURGERY AND ORAL SURGERY EQUIPMENT				
3.1	Labioplasty Instrument Set		1	Set	
		SCALPEL HANDLE #3 125MM	2	pc	
		METZENBAUM SCISSORS STR 180MM	1	pc	
		BABY-METZ SCISSORS DEL STR 145MM	1	pc	
		DEL SCISSORS W/TOOTH- BLDFINE130MM	1	pc	
		TC IRIS SCISSORS CVD S/S 110MM	1	pc	
		TC IRIS SCISSORS STR S/S 110MM	1	pc	
		MICRO-ADSON TISSUE FORCEPS 1X2 120MM	1	pc	
		MICRO-ADSON FORCEPS SERR 120MM	1	pc	
		HARTMANN MOSQUITO FCPSDEL CVD100MM	4	pcs	
		HARTMANN MOSQUITO FCSD STR 100MM	4	pcs	
		HALSTED-MOSQUITO FORCEPS DELSTR125MM	5	pcs	
		TC HALSEY NEEDLE HOLDER SERR 130MM	1	pc	
		GILLIES SKIN HOOK SHARP LRG 180MM	1	pc	
		KIDNEY TRAY STAINLESS STEEL 250MM	1	pc	
		LABORATORY DISH 0.063 L	1	pc	
		FRAZIER SUCTLUER- HUB9FR100MMWRK-LGTH	1	pc	
		FRAZIER SUCTLUER- HUB15FR5/100MM LGTH	1	pc	
		TONGUE DEPRESSOR 16MM 145MM	1	pc	
		MAIER FORCEPS W/RCHT STR 260MM	1	pc	
		BACKHAUS TOWEL CLAMP 90MM	5	pcs	
		STEEL RULER 150MM	1	pc	
		SCALPEL HANDLE #3 WITH MEASURE 125MM	1	pc	
		ADSON TISE FCPS DEN-HDL 1X2T.180MM	1	pc	
		METZENBAUM SCISSORS STR 180MM	1	pc	

NO.	Item	Purchaser's Specifications	Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		PLESTER SUCTION CANNULA D:2.0MM 195MM	1	pc	
		HUMBY DERMATOME 365MM	1	pc	
		WALSHAM SEPTUM FORCEPS STR.RT.220MM	1	pc	
		WALSHAM SEPTUM FORCEPS STR.LFT.220MM	1	pc	
		DOYEN ELEVATOR F/ADULT LFT- CVD 175MM	1	pc	
		DOYEN ELEVATOR F/ADULT RT- CVD 175MM	1	pc	
		LABORATORY DISH 0.063 L	1	pc	
		KIDNEY TRAY STAINLESS STEEL 250MM	1	pc	
		STERILIT I OIL SPRAY	1	pc	
		BOTTOM FOR 1/1 CONTAINER HEIGHT:90MM	1	pc	
		FULL-SIZE LID W/RETENTION PLATE SILVER	1	pc	
		REUSABLE FILTER FOR CONTAINER	1	set	
3.2	Palatoplasty Instrument Set		1	Set	
		SCALPEL HANDLE #7 ENGLISH NO.5 160MM	2	pcs	
		KELLY SCISSORS STR S/S 175MM	1	pc	
		DEBAKEY VESSEL SCISSORS 60DG 155MM	2	pcs	
		ADSON-BROWN TISSUE FCPS 120MM	2	pcs	
		BROWN TISSUE FORCEPS 150MM	1	pc	
		STILLE-BARRAYA CV FCPS3X4SERR 180MM	1	pc	
		WILLIGER BONE ELEVATOR 4.2MM BR.140MM	1	pc	
		NEEDLE NOSE PLIERS SERR 140MM	1	pc	
		WIRE CUTTING SCISS 120MM ONE BLD SERR	1	pc	
		MALLET PEEK 230GR.HEAD- D42MM 250MM	1	pc	
		MEAD MALLETREMOV-DISCS 350GR.190MM	1	pc	
		LEXER OSTEOTOME PEEK- HDL5MM225MM	1	pc	
		LEXER OSTEOTOME PEEK- HDL30MM225MM	1	pc	
		LEXER GOUGE PEEK-HDL 5MM225MM	1	pc	
		LEXER GOUGE PEEK-HDL 7MM 225MM	1	pc	

NO.	Item	Purchaser's Specifications	Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		LEXER GOUGE PEEK-HDL 10MM225MM	1	pc	
		LEXER GOUGE PEEK-HDL 15MM 225MM	1	pc	
		LEXER GOUGE PEEK-HDL 20MM 225MM	1	pc	
		LEXER GOUGE PEEK-HDL 25MM225MM	1	pc	
		LEXER GOUGE PEEK-HDL 30MM225MM	1	pc	
		LUER BONE RONGEUR ANG 150MM	1	pc	
		BLUMENTHAL BONE RONGEUR CVD 155MM	1	pc	
		POSITION PCL STRIPPING WIRE W/EYE 290MM	1	pc	
		TWIST DRILL D1.5MM L70/45MM ROUND SHAFT	1	pc	
		TWIST DRILL D2.0MM L100/75MM ROUND SHAFT	1	pc	
		TWIST DRILL D3.5MM L100/75MM ROUND SHAFT	1	pc	
		TC WIRE HOLDING FORCEPS LAT-JAW 170MM	1	pc	
		WHITEHEAD-JENNINGS MOUTH GAG 110MM	1	pc	
		ELEVATOR LFT-CVD 4MM 140MM	1	pc	
		ELEVATOR RT-CVD 4MM140MM	1	pc	
		LABORATORY DISH 0.063 L	1	pc	
		KIDNEY TRAY STAINLESS STEEL 250MM	1	pc	
		STERILIT I OIL SPRAY	1	pc	
		FULL-SIZE LID W/RETENTION PLATE SILVER	1	pc	
		BOTTOM FOR 1/1 CONTAINER HEIGHT:120MM	1	pc	
3.3	Skin Graft Instrument Set		1	Set	
		Kilner scissors, 12 cm	1	pc	
		Mc indoe scissors, 19 cm	1	pc	
		Halsted mosquito, str, 12 cm	4	pcs	
		Halsted mosquito, cvd,12 cm	2	pcs	
		Backhaus towel forceps, 13 cm	12	pcs	
		Forster forceps, str, serr, 25 cm	4	pcs	
		Mc indoe dressing forceps, 15 cm	1	pc	
		Gillies tissue forceps, 1x2T, 15 cm	1	pc	
		Mini langenbeck retr, 17x5 mm, 16cm	1	pc	
		Scalpel handle no.3	1	pc	

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		Scalpel handle no.4		1	pc	
		Schink dermatome, complete		1	pc	
		Schink spare blade only		12	pcs	
		Schink skin str, blade only		1	pc	
		Needle Holder Crile-Wood, TC, STR, 15 cm, 6"		2	pcs	
		Gillies cutan, hook, fig.2, 18 cm		2	pcs	
		Allis forceps, 5x6 teeth, 15 cm		4	pcs	
3.4	Orthognathic Surgery Set			1	Set	
		Power Control Console 2i with Irrigation		1	pc	
		Lever Arm Motor Unit (LAMU)		2	pcs	
		Single Silicone Tubing Set, 12 ft. (Clips Included)		3	pcs	
		Hospital Grade AC Power Cord		1	pc	
		Autoclavable Irrigation Bag Spike		2	pcs	
		OsteoPower Alumium Autoclave Tray		1	pc	
		Series III Straight Drill		1	pc	
		Series III Straight Drill Irrigation Nozzle (LAMU)		1	pc	
		4:1 Universal Pilot Drill		1	pc	
		Lubrication Sleeve for Series III Straight Drill		1	pc	
		Bur, #1/4 Round, 0.5mm x 59mm, Sterile		2	pcs	
		Bur, #4 Round, 1.4mm x 59mm, Sterile		2	pcs	
		Bur, #6 Round, 1.8mm x 59mm, Sterile		2	pcs	
		Bur, #8 Round, 2.3mm x 59mm, Sterile		2	pcs	
		Bur, #10 Round, 2.7mm x 59mm, Sterile		2	pcs	
		Bur, Round, 4.0mm x 59mm, Sterile		2	pcs	
		Bur, Round, 5.0mm x 59mm, Sterile		2	pcs	
		Bur, Round, 6.0mm x 59mm, Sterile		2	pcs	
		Bur, Round, 7.0mm x 59mm, Sterile		2	pcs	
		Bur, #8 Round, 2.3mm x 65mm, Sterile		2	pcs	
		Bur, Round Diamond, 3.0mm x 59mm, Sterile		2	pcs	
		Bur, Round Diamond, 3.5mm x 59mm, Sterile		2	pcs	
		Bur, Round Diamond, 4.0mm x 59mm, Sterile		2	pcs	

NO.	Item	Purchaser's Specifications	Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		Bur, Round Diamond, 4.5mm x 59mm, Sterile	2	pcs	
		Bur, # 6 Round, 1.8mm x 59mm (5 pack)	3	pcs	
		Bur, #8 Round, 2.3mm x 59mm (5 pack)	3	pcs	
		Bur, #10 Round, 2.7mm x 59mm (5 pack)	3	pcs	
		Bur, #8 Round, 2.3mm x 65mm (5 pack)	3	pcs	
		Bur, Oval, 4.0mm x 59mm, Sterile	3	pcs	
		Bur, Pineapple, 6.0mm x 65mm, Sterile	3	pcs	
		Bur, Oval, 4.0mm x 69mm, Sterile	3	pcs	
		Bur, #8 Round 2.3mm x 26mm (5 pack)	3	pcs	
		0.9mm Pilot Drill, OsteoPower™	3	pcs	
		1.0mm Pilot Drill, OsteoPower™	3	pcs	
		1.3mm Pilot Drill, 12mm Stop, OsteoPower™	3	pcs	
		1.3mm Pilot Drill, 16mm Stop, OsteoPower™	3	pcs	
		1.6mm Pilot Drill, OsteoPower™	3	pcs	
		1.6mm Pilot Drill, Long, OsteoPower™	3	pcs	
		2.0mm Pilot Drill, OsteoPower™	3	pcs	
		2.0mm Pilot Drill, Long, OsteoPower™	3	pcs	
		Reciprocating Saw, Quick Release	1	pc	
		Reciprocating Saw Irrigation Nozzle (LAMU)	1	pc	
		0.4mm x 15.7mm Reciprocating Saw Blade, Mini, Sterile	3	pcs	
		0.4mm x 26.3mm Reciprocating Saw Blade, Long Tapered, Sterile	3	pcs	
		0.4mm 26.3mm Reciprocating Saw Blade Short Tapered, Sterile	3	pcs	
		0.6mm x 12.0mm Arced Reciprocating Saw Blade, 4mm Stop, Sterile	3	pcs	
		0.6mm x 17.0mm Arced Reciprocating Saw Blade, 4mm Stop, Sterile	3	pcs	
		Cross Cut Rasp, Reciprocating Saw, Long, Sterile	3	pcs	
		Cross Cut Rasp, Reciprocating Saw, Short, Sterile	3	pcs	

NO.	Item	Purchaser's Specifications	Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		Sagittal Saw	1	pc	
		Oscillating Saw	1	pc	
		Contra Angle Irrigation Nozzle (LAMU)	1	pc	
		Blade, Sag/Osc 4mm/25mm, Sterile	3	pcs	
		Blade, Sag/Osc 7mm/18mm, Arced, Sterile	3	pcs	
		Blade, Sag/Osc 10mm/10mm, Arced, Sterile	3	pcs	
		Blade, Sag/Osc 10mm/19mm, Sterile	3	pcs	
		Blade, Sag/Osc 10mm/27mm, Arced, Sterile	3	pcs	
		Blade, Sag/Osc 10mm/28mm, Arced, Sterile	3	pcs	
		Blade, Sag/Osc 10mm/29mm, Sterile	3	pcs	
		Blade, Sag/Osc 10mm/39mm, Arced, Sterile	3	pcs	
		Blade, Sag/Osc 6mm/10mm, Sterile	3	pcs	
		Blade, Sag/Osc 6mm/14mm, Sterile	3	pcs	
		Blade, Sag/Osc 6mm/19mm, Sterile	3	pcs	
		Blade, Sag/Osc 6mm/26mm, Sterile	3	pcs	
		Blade, Sag/Osc 19mm/29mm, Arced, Sterile	3	pcs	
		Blade Reciprocating, long 32.7mm cut, sterile	3	pcs	
		0.4mm x 26.3mm Reciprocating saw blade, short shaft, sterile	2	pcs	
		0.4mm x 26.3mm Reciprocating saw blade long shaft, sterile	3	pcs	
		V.R.O. Saw	1	pc	
		V.R.O. Saw Blade, 12mm, .38mm Thick, Sterile	3	pcs	
		V.R.O. Saw Blade, 7mm, Sterile	3	pcs	
		V.R.O. Saw Blade, 12mm, Sterile	3	pcs	
		Senn-Green Retractor, 15cm, 20 x 6mm	2	pcs	
		Langenbeck Retractor, 21cm, 30 x 11mm	2	pcs	
		Obwegeser Soft Tissue Retractor, curved up, 22 cm, 7 x 25 mm	1	pc	
		Obwegeser Soft Tissue Retractor, curved down, 22 cm, 7 x 25 mm	1	pc	
		Mini-Lambotte Osteotome, straight, 17cm, 3mm	1	pc	

NO.	Item	Purchaser's Specifications	Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		WILLIGER Raspatory, 4mm, 16cm	2	pcs	
		CUSHING Raspatory, 15mm, 19cm, round cutting, slightly curved	1	pc	
3.5	Maxillofacial Trauma Instrument Set		1	Set	
		TAPERLOCK™ Screwdriver Body	2	pcs	
		Rigid Mini Plate Cutter	1	pc	
		Plate Cutter	1	pc	
		Calibrated Micro/Mini Plate Bender	1	pc	
		Small Grasping Forceps	2	pcs	
		1.2mm Plate Holder	1	pc	
		1.6mm Plate Holder	1	pc	
		2.0mm Plate Holder	1	pc	
		3 Prong Mini Plate Bender (only for use with 210-0032, 210-0034, 210-00232)	1	pc	
		3 Prong MidFace/Micro Plate Bender	1	pc	
		Right Angle Plate Bender	2	pcs	
		Plate Bending Forceps	2	pcs	
		M4 Autoclave Tray, Series II	1	pc	
		Plate Holding Forceps	2	pcs	
		2.0/2.4mm Fracture Plate Bending Plier, Ratchet	1	pc	
		2.0/2.4mm Fracture Plate Bending Plier	1	pc	
		Clamping Cheek Retractor	1	pc	
		Cheek Retractor, u-shaped, Trauma Tray	1	pc	
		Reduction Forceps	1	pc	
		Modular Handle, Cannula	1	pc	
		Modular Cannula, Short Pointed	1	pc	
		Modular Cannula, Long Pointed	1	pc	
		Trocar, Long Pointed	1	pc	
		Trocar, Short Pointed	1	pc	
		2.4mm Neutral Drill Guide	1	pc	
		Plate to Bone Holding Forceps, Left	1	pc	
		Plate to Bone Holding Forceps, Right	1	pc	
		Universal Plate Bender	1	pc	
		Recon Plate Roller Bender	1	pc	
		Reconstruction Plate Bending Plier, w/ ratchet	1	pc	

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		Depth Gauge, M4/M3-X/Mandible		1	pc	
		Reconstruction Plate Round Cutter Assembly		1	pc	
		Reconstruction Plate Flanged Cutter Assembly		1	pc	
		24 ga. Stainless Steel Wire (QUICK-FIX™)		1	pc	
		2.0mm MMF AUTO-DRIVE® Screw M4 Organizer		1	pc	
		2.0mm x 8mm MMF AUTO-DRIVE® Screw		8	pcs	
		2.0mm x 11mm MMF AUTO-DRIVE® Screw		4	pcs	
		6mm Hohmann Retractor		1	pc	
		8mm Hohmann Retractor		1	pc	
		3mm Periosteal Elevator, Straight Edge		1	pc	
		3mm Periosteal Elevator, Curved Edge		1	pc	
		Sharp Hook		1	pc	
		Termite Forceps		1	pc	
		Reduction Forceps		1	pc	
		M4 Mid-Face Plate Organizer, Series II		1	pc	
		1.6mm Screw VISIDISK™ (WHITE)		1	pc	
		1.6mm Screwdriver Shaft, Long, Manual		2	pcs	
		1.6mm Screwdriver Shaft, Manual		2	pcs	
		M4 Mini Plate Organizer, Series II		1	pc	
		2.0mm Screw VISIDISK™ (BLUE)		1	pc	
		2.0/2.4mm Screwdriver Shaft, Manual		2	pcs	
		2.0mm Locking Screw VISIDISK™ (BLUE)		1	pc	
		M4 Maxi Plate Organizer, Series II		1	pc	
		2.4mm Screw VISIDISK™ (GREEN)		1	pc	
		TAPERLOCK™ Body, Mandible, Fixed		1	pc	
		1.6mm AUTO-DRIVE® Screw VISIDISK™ (WHITE)		1	pc	
4	THORACIC SURGERY EQUIPMENT AND CARDIOVASCULAR					
4.1	Thoracotomy Instrument Set			1	Set	
		MAIER FORCEPS W/RCHT CVD260MM		2	pcs	
		BACKHAUS TOWEL CLAMP 110MM		14	pcs	

NO.	Item	Purchaser's Specifications	Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		SCALPEL HANDLE #4 135MM	2	pcs	
		SCALPEL HANDEL #3L	1	pc	
		TC METZENBAUM SCISSORS DEL CVD 180MM	1	pc	
		TC METZENBAUM SCISSORS CVD 200MM	1	pc	
		TC NELSON-METZ SCISSORS CVD 230MM	1	pc	
		TC NELSON-METZ SCISSORS DEL CVD 285MM	1	pc	
		TC SUTURE WAVECUT SCISSORS CVD 180MM	1	pc	
		TC SUTURE SCISS W/1 SERR CVD 230MM	1	pc	
		TC MAYO-LEXER SCISSORS CVD 165MM	1	pc	
		SURGICAL SCISSORS STR S/B145MM	1	pc	
		TISSUE FORCEPS SERR 145MM	1	pc	
		TISSUE FORCEPS STR 1X2 145MM	2	pcs	
		DISSECT.FORCEPS MED.WIDE 1X2T.200MM	2	pcs	
		TISSUE FORCEPS 1X2 TEETH 250MM MED.	2	pcs	
		DISSECT.FORCEPS MED.WIDE 1X2T.300MM	2	pcs	
		DEBAKEY ATR.FCPS 2.0MM STR150MM	2	pcs	
		DEBAKEY ATR.FCPS 2.0MM STR 200MM	2	pcs	
		DEBAKEY ATR.FCPS 2.0MM STR240MM	2	pcs	
		DEBAKEY ATR.FCPS 2.8MM STR240MM	2	pcs	
		DEBAKEY ATR.FCPS 2.8MM STR 300MM	2	pcs	
		HALSTED-MOSQUITO FORCEPS DEL CVD125MM	6	pcs	
		KOCHER FORCEPS STR 1X2 140MM	6	pcs	
		KOCHER-OCHSNER FORCEPS STR 1X2 200MM	2	pcs	
		KOCHER-OCHSNER FORCEPS STR 1X2240MM	2	pcs	
		MAIER FORCEPS W/RCHT STR 260MM	4	pcs	
		MIKULICZ PERITONEUM FORCEPS CVD.200MM	4	pcs	
		OVERHOLT-GEISS SUTURE FCPS #1CVD205MM	1	pc	
		OVERHOLT-GEISS SUTURE FCPS #2CVD210MM	1	pc	

NO.	Item	Purchaser's Specifications	Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		OVERHOLT-GEISS SUTURE FCPS #3 CVD229MM	1	pc	
		OVERHOLT-GEISS SUTURE FCPS #6 CVD225MM	1	pc	
		OVERHOLT-GEISS SUTURE FCPS#1CVD261MM	1	pc	
		OVERHOLT-GEISS SUTURE FCPS#3CVD276MM	1	pc	
		RUMEL SUTURE FORCEPS HVY-CV 240MM	1	pc	
		RUMEL SUTURE FORCEPS RT-ANG# 5 240MM	1	pc	
		ZENKER SUTURE FORCEPS SLT-CVD 300MM	1	pc	
		ATR.OVUM FORCEPS STR SM250MM	6	pcs	
		DEBAKEY TANGENTIAL CLMP1.38MM-WD220MM	1	pc	
		DEBAKEY TNGENTAL CLMP 2.48MM-WIDE 265MM	1	pc	
		DEBAKEY TANGENTAL CLMP 54/99/270MM	1	pc	
		DEBAKEY ATR.COARCT.CLANG15DG80/240 MM	1	pc	
		DEBAKEY CLAMP 60DG 65/100MM 280MM	1	pc	
		DEBAKEY CLAMP 90DG 72/92MM 255MM	1	pc	
		ALLIS ATR.FORCEPS 8.4MM 220MM	2	pcs	
		COLLIN ATR.FORCEPS 195MM	2	pcs	
		TC CRILE-WOOD NDL HLDSTRSERR 145MM	1	pc	
		TC DEBAKEY NDL HOLDER DEL SERR 180MM	1	pc	
		TC DEBAKEY NDL HOLDER DEL SERR 260MM	1	pc	
		TC DEBAKEY NDL HOLDER DEL SERR 305MM	1	pc	
		TC MAYO-HEGAR NDL HOLDERHVYSERR205MM	2	pcs	
		DUROGRIP NEEDLE H.F/STERNUM-SUTURE 175MM	1	pc	
		REILL CUTTERF/WIRE CLOSE BONE2/1.5/175MM	1	pc	
		KOCHER RETR 4-PRGSEMI-S16X20222MM	2	pcs	
		ROUX RETRACTOR3/SET 165MM	1	set	
		LANGENBECK RETRACTOR 40X10MM	2	pcs	
		SAUERBRUCH RETRACTOR SOLID 55X22MM229MM	2	pcs	

NO.	Item	Purchaser's Specifications	Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		SAUERBRUCH RETRACTOR SOLID 72X19MM229MM	2	pcs	
		CORYLLOS RETRACTOR OPEN 115X65MM255MM	2	pcs	
		CUSHING SADDLE HOOK 22X15MM 250MM	1	pc	
		DEBAKEY RIB SPREADER COMPLETE200X225MM	1	pc	
		ALLISON LUNG SPATULA 54MM 320MM	1	pc	
		ALLISON LUNG SPATULA 137MM300MM	1	pc	
		HARNGTN LNG SPATULA FLX 123X45MM295MM	1	pc	
		BRUNNER RIB SHEARS 340MM	1	pc	
		DOYEN ELEVATOR F/ADULT LFT- CVD 178MM	1	pc	
		DOYEN ELEVATOR F/ADULT RT- CVD 178MM	1	pc	
		FARABEU RASPARTORY CVD.12.5MM BR.145MM	1	pc	
		SEMB ELEVATOR 12MM 231MM	1	pc	
		SEMB ELEVATOR LONG 13MM 230MM	1	pc	
		SEMB BONE-HOLDING FORCEPS190MM8MM	1	pc	
		LISTON BONE-CUTTING FORCEPS CVD 240MM	1	pc	
		LUER-STILLE BONE RONGEUR CVD 225MM	1	pc	
		BAILEY RIB SPRDR / CONTRACTORADULT 200MM	1	pc	
		LEBSCHER STERNUM CHISEL 250MM	1	pc	
		MALLET REMOV-DISCS 340GR.30MM 235MM	1	pc	
		LABORATORY DISH 0.4 L	2	pcs	
		KIDNEY TRAY STAINLESS STEEL 250MM	1	pc	
		REDON SPIKE CH.12 STRONG CVD.KNIFE TIP	1	pc	
		REDON SPIKE CH.14 STRONG CVD.KNIFE TIP	1	pc	
		REDON SPIKE CH.16 STRONG CVD.KNIFE TIP	1	pc	
		YANKAUER SUCTION CANNULA 2.0MM 285MM	1	pc	
		FULL-SIZE LID W/RETENTION PLATE SILVER	1	pc	
		BOTTOM FOR 1/1 CONTAINER HEIGHT:135MM	1	pc	
		1/1 BASKET W/O STACK.FEET 540X253X64MM	1	pc	

NO.	Item	Purchaser's Specifications	Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		SINGLE USE PAPER FILTER WITH INDICATOR	1	pc	
4.2	Vascular Instrument Set		1	Set	
		MAIER FORCEPS W/RCHT CVD260MM	2	pcs	
		BACKHAUS TOWEL CLAMP 110MM	8	pcs	
		SCALPEL HANDLE #4 135MM	2	pcs	
		SCALPEL HANDLE #3 125MM	1	pc	
		JAMESON TENOTOMY SCISSOR CVD/B150MM	1	pc	
		TC IRIS SCISSORS CVD S/S 110MM	1	pc	
		POTTS-DE MARTEL SCISSORS 45DGS/S 185MM	1	pc	
		TC BABY-METZ SCISSORS DELCVD/B 145MM	1	pc	
		TC METZENBAUM SCISSORS DEL CVD 180MM	1	pc	
		TC METZENBAUM SCISSORS CVD 200MM	1	pc	
		TC SUTURE WAVECUT SCISSORS CVD 180MM	1	pc	
		TC MAYO-LEXER SCISSORS CVD 165MM	1	pc	
		SURGICAL SCISSORS STR S/B 145MM	1	pc	
		TISSUE FORCEPS SERR 145MM	1	pc	
		TISSUE FORCEPS STR 1X2 145MM	2	pcs	
		DISSECT. FORCEPS MED.WIDE 1X2T.200MM	2	pcs	
		ULTRA-LIGHT FORCEPS 1.2 MM150MM	2	pcs	
		DEBAKEY ATR.FCPS 2.0MM STR150MM	2	pcs	
		ULTRA-LIGHT FORCEPS 1.5MM 200MM	2	pcs	
		DEBAKEY ATR.FCPS 2.0MM STR 200MM	2	pcs	
		KOCHER FORCEPS STR 1X2 140MM	6	pcs	
		HALSTED-MOSQUITO FORCEPS DEL CVD 125MM	6	pcs	
		KOCHER-OCHSNER FORCEPS STR 1X2 200MM	2	pcs	
		OVERHOLT FORCEPS # 0 CVD 215MM	2	pcs	
		OVERHOLT FORCEPS # 1 CVD 209MM	2	pcs	
		OVERHOLT FORCEPS # 2 CVD 220MM	2	pcs	
		MICRO-ADSON SUTURE FORCEPS CVD 140MM	1	pc	

NO.	Item	Purchaser's Specifications	Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		BABY-MIXTER FORCEPS HEAVY-CVD180MM	1	pc	
		GEMINI CLAMP RT-ANG 140MM	1	pc	
		GEMINI CLAMP RT-ANG 180MM	1	pc	
		TC BABY-CRILE-WOOD NDL HLDR SERR 150MM	1	pc	
		TC DEBAKEY NDL HOLDER DEL SERR 180MM	1	pc	
		TC MAYO-HEGAR NDL HOLDER HVY SERR 205MM	2	pcs	
		TC RYDER NEEDLE HOLDER X-DEL SERR 155MM	1	pc	
		HOOK 4-PRONG SHARP SM-CVD 165MM	2	pcs	
		DESMARRES RETRACTOR 11X14MM 140MM	2	pcs	
		ROUX RETRACTOR 3/SET 165MM	1	set	
		LANGENBECK RETRACTOR 28X14MM	2	pcs	
		LANGENBECK RETRACTOR 40X10MM	2	pcs	
		KOCHER-LANGENBECK RETR 55X11MM 216MM	2	pcs	
		VOLKMANN RETR4-PRGSEMI-S8.5X19 222MM	2	pcs	
		CUSHING VEIN RETRACTOR 10X13MM 203MM	2	pcs	
		ADSON LAMIN RETR 5X4 SEMI-S 325MM	1	pc	
		SELF-RETAINING RETR 3X4T.BLUNT 240MM	1	pc	
		ADSON-BABY RETRACTOR 3X4 BLUNT 140MM	1	pc	
		FREER ELEVATOR S/B 185MM	1	pc	
		VASCULAR SPATULA 3MM BLUNT185MM	1	pc	
		DAVIS VASCULAR SPATULA 245MM	1	pc	
		CRILE VESSEL HOOK BLUNT 90DEG 6/200MM	1	pc	
		DOUBLE-ENDED PROBE 1.5MM 180MM	1	pc	
		SCHMID IRRIGATING CANNULA MALLEAB.LL.	1	pc	
		MICRO ATR. BULLDOG CLAMP STR.10/50MM	2	pcs	
		MICRO ATR. BULLDOG CLAMP ANG.10/45MM	2	pcs	
		MICRO ATR. BULLDOG CLAMP STR.20/60MM	2	pcs	
		MICRO ATR. BULLDOG CLAMP ANG.20/55MM	2	pcs	

NO.	Item	Purchaser's Specifications	Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		MICRO ATR. BULLDOG CLAMP CVD.20/55MM	2	pcs	
		DEBAKEY ATR. BULLDOG CLAMP CVD.20/78MM	2	pcs	
		DEBAKEY ATR. BULLDOG CLAMP CVD.30/86MM	2	pcs	
		ALPHA VASCULAR CLAMP ANGLED 350 GRAMS	2	pcs	
		ALPHA VASCULAR CLAMP SLT CURVED350 GRAM	2	pcs	
		ALPHA VASCULAR CLAMP CURVED 350 GRAMS	2	pcs	
		DEBAKEY PERIPHERAL CLAMP 60DG180MM	2	pcs	
		DERRA PEDIATRIC FORCEPS 26MM175MM	1	pc	
		COOLEY PEDIATRIC CLAMP 60DG 30/160MM	1	pc	
		ALLIS ATR. FORCEPS 6.2MM 155MM	2	pcs	
		PELKMANN FORCEPS CVD SERR261MM	1	pc	
		LABORATORY DISH 0.4 L	2	pcs	
		KIDNEY TRAY STAINLESS STEEL 250MM	1	pc	
		REDON SPIKE CH.10 SLIG.CVD.TRIANG.TIP	1	pc	
		REDON SPIKE CH.12 SLIG.CVD.TRIANG.TIP	1	pc	
		FULL-SIZE LID W/RETENTION PLATE SILVER	1	pc	
		BOTTOM FOR 1/1 CONTAINER HEIGHT:135MM	1	pc	
		1/1 BASKET W/O STACK. FEET 540X253X64MM	1	pc	
		SINGLE USE PAPER FILTER WITH INDICATOR	1	pc	
4.3	Costa Clip Set		1	Set	
		SHAPP Plate (All Size)	15	pcs	
		Container Box	1	pc	
		Applicator Curved	1	pc	
		Applicator Straight	1	pc	
		Applicator APM	1	pc	
5	PEDIATRIC SURGERY EQUIPMENT				
5.1	Minor Instrument Set		1	Set	
		SCALPEL HANDLE #3 125MM	2	pcs	
		SURGICAL SCISSORS STR S/B145MM	2	pcs	
		MAYO SCISSORS STR 140MM	2	pcs	
		MAYO SCISSORS CVD 140MM	2	pcs	

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		METZENBAUM SCISSORS CVD180MM		2	pcs	
		TISSUE FORCEPS SERR 145MM		2	pcs	
		STANDARD FORCEPS SERR 145MM		2	pcs	
		STANDARD FORCEPS SERR 180MM		2	pcs	
		STANDARD TISSUE FORCEPS 1X2 145MM		2	pcs	
		STANDARD TISSUE FORCEPS 1X2 180MM		2	pcs	
		FOERSTER-BALLENGR SPNG FCPSERSTR180MM		2	pcs	
		BACKHAUS TOWEL CLAMP 90MM		4	pcs	
		HALSTED-MOSQUITO FORCEPS DELSTR125MM		4	pcs	
		CRILE FORCEPS CVD 140MM		2	pcs	
		SPENCER-WELLS FORCEPS STR130MM		6	pcs	
		KOCHER-OCHSNER FORCEPS STR 1X2 160MM		2	pcs	
		KOCHER-OCHSNER FORCEPS STR 1X2 185MM		2	pcs	
		CRILE-WOOD NDHLDRFINE- SERR150MM		1	pc	
		CRILE-WOOD NEEDLE HOLDERHVV-SERR160MM		1	pc	
		DIRECTOR W/TONGUE STR 145MM		2	pcs	
		MYRTLE-LEAF PROBE 2.0MM 145MM		2	pcs	
		SENN-MILLER RECTOR.SH.8X7/18X5.5MM		2	pcs	
		FARABEUF RTRCTRS 25X10/32X12-22X10/28X12		2	set	
		BOSE TRACHEAL LFT- HOOK165MM		2	pcs	
		LANGENBECK RETRACTOR OPEN28X10MM209MM		2	pcs	
		ALLIS FORCEPS 4X5 155MM		2	pcs	
		VOLKMANN BONE CURETTE #00002.8MM170MM		1	pc	
		SINGLE USE PAPER FILTER WITH INDICATOR		1	pc	
		1/1 BASKET W/O STACK FEET 540X253X44MM		1	pc	
		BOTTOM FOR 1/1 CONTAINER HEIGHT:135MM		1	pc	
		FULL-SIZE LID W/RETENTION PLATE SILVER		1	pc	

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
5.2	Infant Laparotomy Instrument Set			1	Set	
		Scalpel Handel #3		2	pcs	
		Op Sciss 5 1/2" Str Sh/bl		1	pc	
		Halsted Mosq Fcp Str 5"		6	pcs	
		Halsted Mosq Fcp Cvd 5"		6	pcs	
		Crile Fcp Str 5 1/2"		4	pcs	
		Crile Fcp Cvd 5 1/2"		4	pcs	
		Kocher Fcp Str Del 1x2 5 1/2"		3	pcs	
		Kocher Fcp Cvd Del 1x2 1/2"		3	pcs	
		Metz Lahey Del Crv Sciss 5 3/4		1	pc	
		Metzenbaum Sciss Del Cvd 7"		1	pc	
		Roch Pean Str Del 5 1/2"		3	pcs	
		Roch Pean Cvd Del 5 1/2"		3	pcs	
		Semkin Dress Fcp Nar 5"Serr		1	pc	
		Semkin Tiss Fcp Nar 1x2 5"		1	pc	
		Babcock Fcp 5 1/2"		3	pcs	
		Allis Tiss Fcp Del 4x5 6"		3	pcs	
		Yankauer Suct Tub Ped		1	pc	
		Miller Senn Retr Shrp D/e 6"		1	pc	
		Miller Senn Retr Blnt D/e 6"		1	pc	
		Balfour Retr 1 1/4" Pediatric		1	pc	
		Adson Tiss Fcp 1x2 Del 4 3/4"		1	pc	
		Adson Dress Fcp Serr Del 4 3/4"		1	pc	
		Parker De Retr 5/8x5 set/2		1	pc	
		Zalkind Ribbon Retr 1/2"x7.75"		1	pc	
		Zalkind Ribbon Retr 3/4"x7.75"		1	pc	
		Ballengr Spng Fcps Str Serr 7"		2	pcs	
6	ONCOLOGY SURGERY EQUIPMENT					
6.1	Mastectomy Instrument Set			1	Unit	
		FOERSTER SPONGE FCPS SERR STR 245MM		6	pcs	
		BACKHAUS TOWEL CLAMP 135MM		10	pcs	
		SCALPEL HANDLE #3 125MM		1	pc	
		SCALPEL HANDLE #4 135MM		2	pcs	
		TC MAYO SCISSORS STR 170MM		1	pc	
		TC MAYO SCISSORS CVD 170MM		2	pcs	
		TC METZENBAUM SCISSORS CVD 145MM		1	pc	
		SURGICAL SCISSORS STR S/B145MM		2	pcs	
		STANDARD FORCEPS SERR 145MM		1	pc	
		STANDARD FORCEPS SERR 200MM		1	pc	

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		STANDARD TISSUE FORCEPS 1X2 145MM		1	pc	
		STANDARD TISSUE FORCEPS 1X2T.200MM		1	pc	
		ALLIS FORCEPS 5X6 155MM		10	pcs	
		HALSTED-MOSQUITO FORCEPS DEL CVD125MM		10	pcs	
		CRILE FORCEPS CVD 140MM		10	pcs	
		ROCHESTER-PEAN FORCEPS CVD 160MM		6	pcs	
		CZERNY RETRACTOR 38X22MM 175MM		6	pcs	
		KELLY RETRACTOR OPEN 50X38MM261MM		2	pcs	
		KELLY RETRACTOR OPEN 64X54MM261MM		2	pcs	
		US-ARMY RETRAC.26X15/43X15- 23X15/40X15		1	pc	
		KOCHER RETR 4-PRGSEMI- S16X20222MM		1	pc	
		POOL SUCTION CANNULA CHARR.30		1	pc	
		MAYO-HEGAR NEEDLE HOLDER150MM		4	pcs	
		SINGLE USE PAPER FILTER WITH INDICATOR		1	pc	
		1/1 BASKET W/O STACK FEET 540X253X44MM		1	pc	
		BOTTOM FOR 1/1 CONTAINER HEIGHT:135MM		1	pc	
		FULL-SIZE LID W/RETENTION PLATE RED		1	pc	
7	ENT EQUIPMENT					
7.1	Advance FESS Instrument Set			1	Set	
		Trocar for Sinoscopy, fenestrated beak	: Trocar for Sinoscopy, fenestrated beak			
		Antrum Curette oblong	: Antrum Curette, oblong, small size, length 19 cm			
		HOPKINS®II Telescope 45°, 4 mm, 18 cm	: HOPKINS®II Telescope 45°, 4 mm, 18 cm			
		HOPKINS®II Telescope 30°, 4 mm, 18 cm	: HOPKINS®II Telescope 30°, 4 mm, 18 cm			
		HOPKINS®II Telescope 0°, 4 mm, 18 cm	: HOPKINS®II Telescope 0°, 4 mm, 18 cm			
		Bipolar Coagulating Forceps, 19 cm	: Bipolar Coagulating Forceps, 19 cm			
		Suction Tube, Ø 2.5mm, 13 cm	: Suction Tube, Ø 2.5 mm, 13 cm			

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		Suction Tube, 9 Fr., 10 cm	: FRAZIER Suction Tube, with mandrel and cut-off hole, with distance marking at 5 - 9 cm, 9 Fr., working length 10 cm			
		Antrum Cannula, 4 mm, 12.5 cm	: v. EICKEN Antrum Cannula, LUERLock, with cut-off hole, short curve, outer diameter 4 mm, length 12.5 cm			
		Antrum Cannula, 3 mm, 12.5 cm	: v. EICKEN Antrum Cannula, LUERLock, with cut-off hole, short curve, outer diameter 3 mm, length 12.5 cm			
		Antrum Cannula, Ø 3 mm, 12.5 cm	: Antrum Cannula, Ø 3 mm, 12.5 cm			
		Antrum Cannula, Ø 2.5 mm, 12.5 cm	: v. EICKEN Antrum Cannula, LUERLock, long curved, malleable, serrated grip plate, outer diameter 2.5 mm, length 12.5 cm			
		Antrum Curette, small	: Antrum Curette, small			
		Frontal Sinus Curette, 90° curved	: Frontal Sinus Curette, 90° curved			
		Frontal Sinus Curette, 55° curved	: KUHN-BOLGER Frontal Sinus Curette, 55° curved, oval, forward cutting, length 19 cm			
		Probe, double-ended, 19 cm	: Probe, double-ended, maxillary sinus ostium seeker, ball-shaped ends diameter 1.2 and 2 mm, length 19 cm			
		Sickle Knife, pointed, 19 cm	: Sickle Knife, pointed, 19 cm			
		Elevator, doubleended, 20 cm	: Elevator, double-ended, 20 cm			
		RHINOFORCE® II Double Spoon Forceps	: RHINOFORCE® II Double Spoon Forceps			
		RHINOFORCE® II Double Spoon Forceps	: STAMMBERGER RHINOFORCE® II Double Spoon Forceps, vertical opening, 65° upturned, spoon diameter 3 mm, with cleaning connector, working length 12 cm			
		Punch, circular, 65°, 3.5 mm	: Punch, circular, 65°, 3.5 mm			
		Punch, circular, dia. 4.5 mm	: Punch, circular, dia. 4.5 mm			
		Suction Punch, size 1	: Suction Punch, size 1			
		Suction Punch, size 1	: Suction Punch, size 1			

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		RHINOFORCE® II Nasal Scissors, 13 cm	: RHINOFORCE® II Nasal Scissors, 13 cm			
		Antrum Grasping Forceps, downwards	: HEUWIESER Antrum Grasping Forceps, jaws curved downwards, fixed jaw curved 90°, movable jaw backward opening 120°, with cleaning connector, working length 10 cm			
		Antrum Punch, left down	: Antrum Punch, left down			
		Antrum Punch, right down	: Antrum Punch, right down			
		RHINOFORCE® II Antrum Punch	: RHINOFORCE® II Antrum Punch			
		RHINOFORCE®II Antrum Punch	: RHINOFORCE®II Antrum Punch			
		RHINOFORCE® II Nasal Cut. Forceps, 13 cm	: RHINOFORCE® II Nasal Cut. Forceps, 13 cm			
		RHINOFORCE®II Nasal Forceps, size 0	: GRÜNWARD-HENKE RHINOFORCE® II Nasal Forceps, 45° upturned, through-cutting, tissue-sparing, BLAKESLEY shape, size 0, width 3 mm, with cleaning connector, working length 13 cm			
		RHINOFORCE®II Nasal Forceps, size 0	:RHINOFORCE®II Nasal Forceps, size 0			
		RHINOFORCE® II Nasal Forceps, size 1	: RHINOFORCE® II Nasal Forceps, size 1			
		RHINOFORCE® II Nasal Forceps, size 1	: BLAKESLEY-WILDE RHINOFORCE® II Nasal Forceps, 45° upturned, size 1, with cleaning connector, working length 13 cm			
		RHINOFORCE® II Nasal Forceps, size 1	: BLAKESLEY RHINOFORCE® II Nasal Forceps, straight, size 1, with cleaning connector, working length 13 cm			
		Protection Tube	: Protection Tube			
		Needle, Septum, angular	: Needle, Septum, angular			
		Bipolar High Frequency Cord, 300 cm	: Bipolar High Frequency Cord, 300 cm			
		FREER Elevator, double-ended	:FREER Elevator, double-ended, semisharp and blunt, length 20 cm			
7.2	Mastoidectomy Instrument Set + Bur Included			1	Set	
		COTTLE Metal Mallet, 18 cm	: COTTLE Metal Mallet, 18 cm	1	pc	

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		Tissue Forceps, atraumatic, 12 cm	: Tissue Forceps, atraumatic, 12 cm	1	pc	
		Scissors	: Scissors	1	pc	
		Scissors, curved, 10.5 cm	: Scissors, curved, 10.5 cm	1	pc	
		Scissors, curved, 14 cm	: Scissors, curved, 14 cm	1	pc	
		Forceps, 4x 5 teeth, 15 cm	: Forceps, 4x 5 teeth, 15 cm	2	pcs	
		Tissue Forceps	: Tissue Forceps	1	pc	
		Dressing Forceps	: Dressing Forceps	1	pc	
		Blade, sterile, 100 pcs	: Blade, sterile, 100 pcs	1	pc	
		Blade, sterile, 100 pcs	: Blade, sterile, 100 pcs	1	pc	
		Dressing Forceps	: Dressing Forceps	1	pc	
		Artery Forceps, 1x 2 teeth, 14 cm	: Artery Forceps, 1x 2 teeth, 14 cm	2	pcs	
		Artery Forceps, anatomic	: Artery Forceps, anatomic	6	pcs	
		Dressing/Sponge Holding Forceps, 21 cm	: Dressing/Sponge Holding Forceps, 21 cm	1	pc	
		Tissue Forceps	: Tissue Forceps	1	pc	
		Tissue Forceps	: Tissue Forceps	1	pc	
		LANGENBECK Retractor, 33 x 14 mm	: LANGENBECK Retractor, 33 x 14 mm	2	pcs	
		Suction Tube, 12 Fr.	: Suction Tube, 12 Fr.	1	pc	
		Retractor	: Retractor	2	pcs	
		Needle Holder, 15 cm	: Needle Holder, 15 cm	1	pc	
		Scissors, curved, 14 cm	: Scissors, curved, 14 cm	1	pc	
		Mosquito Artery Forceps, curved	: Mosquito Artery Forceps, curved	6	pcs	
		Towel Forceps, 11 cm	: Towel Forceps, 11 cm	6	pcs	
		Tissue Forceps	: Tissue Forceps	1	pc	
		Cup Medicine	: Cup Medicine	1	pc	
		Cup Medicine	: Cup Medicine	1	pc	
		FREER Elevator, double-ended	: FREER Elevator, double-ended, semisharp and blunt, length 20 cm	1	pc	
		TRAUTMANN Mastoid Gouge, 14 cm	: TRAUTMANN Mastoid Gouge, 14 cm	1	pc	
		TRAUTMANN Mastoid Gouge, 14 cm	: TRAUTMANN Mastoid Gouge, 14 cm	1	pc	
		TRAUTMANN Mastoid Gouge, 14 cm	: TRAUTMANN Mastoid Gouge, 14 cm	1	pc	
		JANSEN Rongeur, bayonet, 17 cm	: JANSEN Rongeur, bayonet, 17 cm	1	pc	
		Nasal Speculum for adults, 13 cm	: Nasal Speculum for adults, 13 cm	1	pc	
		Surgical Handle, Fig. 3, 12.5 cm	: Surgical Handle, Fig. 3, 12.5 cm	1	pc	
		Needle Holder, 13 cm	: Needle Holder, 13 cm	1	pc	
		Suction Tube, 9 Fr.	: Suction Tube, 9 Fr.	1	pc	
		Scissors, extra delicate, curved, 10 cm	: Scissors, extra delicate, curved, 10 cm	1	pc	
		Scissors, curved, 15 cm	: Scissors, curved, 15 cm	1	pc	

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)	
				1	Unit		
7.3	Otoacoustic Emissions (Diagnostic DPOAE + TEOAE)						
		Diagnostic DPOAE	: 4 Configurable Protocols				
		Frequencies	: 1.5 - 12 kHz				
		Intensity	: 40-70 dB SPL				
		SNR	: 3-10 dB				
		Averaging Times	: 0.5 , 1,2,4 sec				
		Frequency for pass	: 0-6				
		Screening DPOAE	: 1 Fixed Protocols				
		Frequencies	: 2,3,4,5 kHz				
		Intensity	: 65/55 dB				
		SNR	: 6 dB				
		Pass	: 3 out of 4 frequencies				
		Diagnostic TEOAE	: 2 Configurable Protocols				
		Frequencies	: 0.7 - 4 kHz				
		Intensity	: 83 dB pe SPL				
		SNR	: 3-10 dB				
		Averaging Times	: 8, 16, 32, 64 sec				
		Frequency for pass	: 0-6				
		Screening TEOAE	: 1 Fixed Protocols				
		Frequencies	: 1.5 - 4 kHz				
		Intensity	: 83 dB pe SPL				
		SNR	: 4 dB				
		Pass	: 3 out of 6 frequencies				
		Handheld Unit					
		Display	: Color OLED display				
		User Input	: 4-button operation				
Connectors	: Micro-USB for charging and communication						
	HDMI for probe						
Weight	approx 180 g						
Comunnication to PC	: Micro - USB						
Languages	: English, German, Spanish, French, Polish, Russian, Italian, Turkish, Portuguese, Chinesse						
Power Supply	: 5.0V DC, 1.6 A						
Probe							
Connector	: HDMI						
Probe Description	: Integrated Microphone and receivers in probe head						
	calibration data stored on probe						
	Cable length	: approx. 102 cm					

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		weight	: approx. 28 g			
		Microphone Noise	: 20 dB SPL @ 2 kHz (1 Hz Bandwidth), -13 dB SPL @ 1 kHz (1 Hz bandwidth)			
		Ear tips	: Single Use disposables ear tips			
		Data				
		Test memory	: 250 tests on Unit			
		Patient names	: Patient names on Unit (Optional)			
		Database software	: Report output to PDF, RTF, Image files			
		Printer				
		Type	: Thermal Dot Matrix			
		Power	: 7.4 V lithium ion battery 100-240 V, 50/60 Hz			
		Paper width	: approx. 57 mm			
		Communication	: Bluetooth			
		Power				
		Battery	: 3.6 V rechargeable lithium ion			
		Battery life	: 15 hours on time			
		Charge time	: 4 hours to 100%			
		Accessories				
		Standard	: Hand-held unit, Probe, Micro USB cables for charger and database, Database software,			
			Disposable ear tip kit and tubes, User Manual, Quick Guide, Calibration Certificate			
8	UROLOGICAL EQUIPMENT					
8.1	Endomat LC SCB or similar			1	Unit	
		Bottle Stand, for suction bottle	: Bottle Stand, for suction bottle 20300051 for use with Endomat LC	1	pc	
		Cap for Suction Bottle 20300051	: Bottle Cap, for Suction Bottle 20300051, for use with ENDOMAT@ LC and UROMAT E.A.S.I.	1	pc	
		Suction Bottle, 0.5 l	: Suction Bottle, 0.5 l, sterilizable, for use with ENDOMAT@ LC and UROMAT E.A.S.I.	1	pc	
		Pump tube, 25 pcs	: Pump tube for Endomat LC, and Unidrive ENT, Eco, NEURO, OMFS package of 25 pieces, sterilizable	1	pc	
		One-Pedal Footswitch	: One-Pedal Footswitch, digital, two- stage	1	pc	

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		Bottle Stand Holder	: Bottle Stand Holder	1	pc	
		Bottle Stand, for bottle 5 l	: Bottle Stand, for suction bottle	1	pc	
		Suction Bottle, 5 l, sterilizable	: Suction Bottle, 5l	1	pc	
		Bottle Cap, 1.5 and 5 l	: Bottle Cap, for suction bottle approx 1.5 and 5l, sterilizable	1	pc	
		ENDOMAT® LC SCB, Urology Set	: ENDOMAT® LC SCB, suction pump, power supply 100 - 240 VAC, 50/60 Hz System requirements: SCB control NEO system with integrated SCB control NEO Software Release 20090001-42 consisting of: 20330320-1 ENDOMAT® LC SCB, with KARL STORZ-SCB 20090170 SCB Connecting Cable, length 100 cm 20300051 Suction Bottle, 0.5 l, sterilizable 20330342 Silicone Tubing Set, for suction, sterilizable, for use with Suction Bottle 20300051 20300039 Bottle Cap, for Suction Bottle 20300051 20300231 Bottle Stand, for Suction Bottle 20300051 20701070 Control Cable	1	pc	
		Tubing Set Calcuson for Endomat LC	: Silicone Tubing Set, for suction, sterilizable, for use with Suction Bottle 20300051 for use with Endomat LC and Calcuson	1	pc	
8.2	URS 8 Fr			1	Unit	
		Intrumen Port, 2 channels	Intrumen Port with Sealing System and Quick Release Lock 2 channels, 1 straight channel, 1 lateral channel	1	pc	
		Forceps, long jaws, 5 Fr., 60 cm	PEREZ-CASTRO, Grasping Forceps, long jaws for Steinstrabe, 3 double action jaws, 5 Fr., rigid, length 60 cm, color code : red	1	pc	
		Biopsy Forceps, 5 Fr., 60 cm	Biopsy Forceps, double action jaws, 5 Fr., rigid, length 60 cm, color code : red	1	pc	
		Forceps, 5 Fr., 60 cm, Large stones	Grasping Forceps for large stones and stone fragments, double action jaws, 5 Fr., rigid length 60 cm, color code : red	1	pc	
		Forceps, 5 Fr., 60 cm	Grasping Forceps for stone fragments, rigid, double action jaws, 5 Fr., length 60 cm, color code : red	1	pc	

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		Cleaning agent, tube 5 gr.	Cleaning agent for distal and proximal lenses and fiber optic surfaces of endoscopes, tube 5 gr.	5	pcs	
		Adaptor for Uretero-Renoscopes	Adaptor, autoclavable, for KARL STORZ ureterorenoscopes, new generation, for use with CALCUSPLIT, in conjunction with Instrument Port 27001 G and Handpiece 27630038	1	pc	
		Seal, 10x	Seal, for Instrument Ports 27001 G/GF/GH/GH, LUER-Adaptor 27014 Y and 26252 BS/BL, package of 10, single use recommended	1	pc	
		Fiber Optic Light Cable, 230 cm, 2,5mm	Fiber Optic Light Cable, with straight connector, diameter 2,5 mm, length 230 cm	1	pc	
8.3	Telecam SL II High Grade			1	Unit	
		Fiber Optic Light Cable, 250 cm, Ø4.8 mm	:Fiber Optic Light Cable, with straight connector, extremely heat-resistant, enhanced light transmission, diameter 4.8 mm, length 250 cm	1	pc	
		Cold Light Fountain XENON NOVA® 300	: Cold Light Fountain XENON NOVA 300, with one 300Watt XENON lamp and one light outlet Power Supply: 100-125/220-240 VAC, 50/60 Hz consisting of: 20134020 XENON NOVA 300 400A Mains Cord	1	pc	
		19" HD Monitor	: approx. 19" HD Monitor, color systems PAL/NTSC, max. screen resolution 1280 x 1024, image format 4:3, power supply 100 - 240 VAC, 50/60 Hz, wall mount with VESA 100 adaptor, including: External 24 VDC Power Supply Mains Cord	1	pc	
		TELECAM One-Chip Camera Head, PAL	: TELECAM One-Chip Camera Head, color system PAL, soakable, gas sterilizable, with integrated Parfocal Zoom Lens, f = 25 - 50 mm (2x), 2 freely programmable camera head buttons	1	pc	

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		TELECAM SL II, EN	: TELECAM SL II Camera Control Unit, color systems PAL/NTSC, with integrated digital Image Processing Module, power supply 100 - 240 VAC, 50/60 Hz, consisting of: 20213020 TELECAM SL II Camera Control Unit 400 A Mains Cord, length 300 cm 536 MK BNC Video Cable, length 200 cm 547 S Vvideo (Y/C) Connecting Cable, length 180 cm 202001231U Keyboard, with US English character set, PS2 Plug	1	pc	
8.4	Lower Urology Set			1	Unit	
		HOPKINS® Telescope 0°, 4 mm, 30 cm	: HOPKINS Straight Forward Telescope 0°, enlarged view, ø 4 mm, autoclavable, fiber optic light transmission incorporated, Color code: green	1	pc	
		HOPKINS® Telescope 30°, 4 mm, 30 cm	: HOPKINS® Forward-Oblique Telescope 30°, diameter 4 mm, length 30 cm, autoclavable, fiber optic light transmission incorporated, color code: red	1	pc	
		HOPKINS® Telescope 70°, 4 mm, 30 cm	: HOPKINS Lateral Telescope 70°, enlarged view, ø 4 mm, autoclavable, fiber optic light transmission incorporated, Colorcode: yellow	1	pc	
		Optical Biopsy Forceps	: Optical Biopsy Forceps, double action jaws	1	pc	
		Catheter Deflecting Mechanism	: Catheter Deflecting Mechanism with 2 lockable channels, with ratchet, filling rod 27021O included	1	pc	
		Cystoscope Sheath, 22 Fr., Set	: Cystoscope-Urethroscope Sheath, 22 Fr., with additional slot, color code: blue consisting of: 27026 BBSheath 27026 BO Obturator and 2 LUER-Lock cones	1	pc	
		Cystoscope Sheath, 25 Fr., Set	: Cystoscope-Urethroscope Sheath, 25 Fr., with additional slot, color code: white consisting of: 27026 AB Sheath 27026 AO Obturator and 2 LUER-Lock cones	1	pc	

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		Working Element	: Working Element (also for use with optical Urethrotome) Motion by means of a spring. The thumb support is movable. In rest position the electrode is inside the sheath.	2	pcs	
		Resectoscope Sheath, 26 Fr., Set	: Resectoscope Sheath, 26 Fr., oblique beak, rotating inner sheath with ceramic insulation, quick release lock, color code: yellow consisting of: 27050 SC Resectoscope Sheath 27050 CA Inner Sheath Connecting Tube for In- and Outflow	1	pc	
		Cutting Loop, 24/26 Fr.	: Cutting Loop angled, 24/26 Fr., color code: yellow	12	pcs	
		Coagulating Electrode, pointed	: Coagulating Electrode pointed, 24/26 Fr. , color code: yellow	3	pcs	
		Coagulating Electrode, Ø 3 mm	: Coagulating Electrode ball-shaped, diameter 3 mm, 24/26 Fr., color code: yellow	3	pcs	
		Obturator, for 27068D	: Obturator, for urethrotome sheath, 21 Fr., 27068D	1	pc	
		SACHSE Urethrotome Sheath, Set	: SACHSE Urethrotome Sheath, 21 Fr., with channel for FILIFORM bougies consisting of: 27068 D SACHSE Urethrotome Sheath and 2 LUER-Lock cones	2	pcs	
		Supplementary Sheath	: Supplementary Sheath, half-round, to insert a balloon catheter, to slip on urethrotome sheath 27068 D	1	pc	
		Knife, straight	: SACHSE Cold Knife straight, not to be used with HF current	1	pc	
		Knife, round	: Cold Knife round, not to be used with HF current	1	pc	
		Stone Crushing Forceps, sgl. Action jaws	: Stone Crushing Forceps, single action jaws	1	pc	
		Lithotrite Set, 24 Fr.	: Lithotrite, incorporating both handle and turning screw action, 24 Fr. consisting of: 27076 A Lithotrite and 2 LUER-Lock cones	1	pc	
		Inflow Tube, length 80 cm	: Inflow Tube, with LUER-Lock connector 27500, ø 9 mm, length 80 cm	1	pc	
		Outflow Tubing, length 140 cm	: Outflow Tubing, diameter 12 mm, length 140 cm	1	pc	
		BENIQUE Urethral Bougie, 28.5 Fr.	: BENIQUE Urethral Bougie, without channel, curved, 28.5 Fr.	1	pc	
		BENIQUE Urethral Bougie, 27 Fr.	: BENIQUE Urethral Bougie, without channel, curved, 27 Fr.	1	pc	

NO.	Item	Purchaser's Specifications	Quantity		Statement of Compliance (Bidder's Offered Item & Specification)	
		BENIQUE Urethral Bougie, 25.5 Fr.	: BENIQUE Urethral Bougie, without channel, curved, 25.5 Fr.	1	pc	
		BENIQUE Urethral Bougie, 24 Fr.	: BENIQUE Urethral Bougie, without channel, curved, 24 Fr.	1	pc	
		BENIQUE Urethral Bougie, 22.5 Fr.	: BENIQUE Urethral Bougie, without channel, curved, 22.5 Fr.	1	pc	
		BENIQUE Urethral Bougie, 21 Fr.	: BENIQUE Urethral Bougie, without channel, curved, 21 Fr.	1	pc	
		BENIQUE Urethral Bougie, 19.5 Fr.	: BENIQUE Urethral Bougie, without channel, curved, 19.5 Fr.	1	pc	
		BENIQUE Urethral Bougie, 18 Fr.	: BENIQUE Urethral Bougie, without channel, curved, 18 Fr.	1	pc	
		BENIQUE Urethral Bougie, 16.5 Fr.	: BENIQUE Urethral Bougie, without channel, curved, 16.5 Fr.	1	pc	
		BENIQUE Urethral Bougie, 15 Fr.	: BENIQUE Urethral Bougie, without channel, curved, 15 Fr.	1	pc	
		BENIQUE Urethral Bougie, 13.5 Fr.	: BENIQUE Urethral Bougie, without channel, curved, 13.5 Fr.	1	pc	
		BENIQUE Urethral Bougie, 12 Fr.	: BENIQUE Urethral Bougie, without channel, curved, 12 Fr.	1	pc	
		BENIQUE Urethral Bougie, 10.5 Fr.	: BENIQUE Urethral Bougie, without channel, curved, 10.5 Fr.	1	pc	
		BENIQUE Urethral Bougie, 9 Fr.	: BENIQUE Urethral Bougie, without channel, curved, 9 Fr.	1	pc	
		Insertion Mandrin	: Insertion Mandrin, for Catheters	1	pc	
		Telescope Bridge	: Telescope Bridge, with 1 lockable channel, for use with Cystoscope Sheaths 27026 A/AB/B/BB/C/CB/D/DB/U	1	pc	
		ELLIK Evacuator	: ELLIK Evacuator	2	pcs	
		Cystoscope Sheath, 20 Fr., Set	: Cystoscope-Urethroscope Sheath, 20 Fr., with slot, color code: red consisting of: 27026 CB Cystoscope-Urethroscope Sheath 27026 CO Obturator and 2 LUER-Lock Cones	1	pc	
8.5	PCN 19 cm			1	Unit	
		Forceps	: Forceps, for grasping larger stones and stone fragments, with serrated jaws and ring handle, double action jaws, 10.5 Fr., length 38 cm, color code: red-black	1	pc	
		Forceps	: Forceps, for grasping larger stones and stone fragments, with fenestrated jaws and ring handle, double action jaws, 10.5 Fr., length 38 cm, color code: red-black	1	pc	

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		Forceps	: Forceps, for grasping larger stones and stone fragments, with triple serrated jaws and U-spring handle, 10.5 Fr., length 38 cm, color code: red-black	1	pc	
		Forceps	: Forceps, for grasping stone fragments and coagula, with fenestrated jaws and U-spring handle, 11.5 Fr., length 38 cm, color code: red-black	1	pc	
		Dilator, 30 Fr. For 27090 A	: Dilator, 30 Fr., for use with 27090	1	pc	
		Dilator, 27 Fr. For 27090 A	: Dilator, 27 Fr., for use with 27090 A	1	pc	
		Telescope Bougie Set	: Telescope Bougie Set, including 6 dilation sleeves 9, 12, 15, 18, 21 and 24 Fr. consisting of: 27090 A Telescope Bougie Set, with 2 rigid and 2 flexible guide rods	1	pc	
		HOPKINS® Telescope 6°	: HOPKINS® Wide Angle Straight Forward Telescope 6°, with angled eyepiece, autoclavable, fiber optic light transmission incorporated with working channel, with LUER-Lock connection for inflow, color code: green-yellow	1	pc	
		Fiber Optic Light Cable, 230 cm, Ø3.5 mm	: Fiber Optic Light Cable, with straight connector, diameter 3.5 mm, length 230 cm	1	pc	
		Hollow Obturator and Fascial Dilator	: Hollow Obturator and Fascial Dilator, Color code: black	1	pc	
8.6	Calcuson Unit			1	Unit	
		CALCUSON Ultrasonic Generator	: CALCUSON Ultrasonic Generator Set, power supply 100 - 120 VAC/200 - 240 VAC, 50/60 Hz consisting of: 27610020 CALCUSON Ultrasonic Generator 400 A Mains Cord 20014230 One- Pedal Footswitch 27610030 Transducer 27610072 Connecting Cable (transducer/generator) 27085 PL Protection Sleeve, for storage and sterilization of probes 27085 CR Cleaning Rod, for probes	1	pc	
		Tubing Set Calcuson for Endomat LC	: Silicone Tubing Set, for suction, sterilizable, for use with Suction Bottle 20300051 for use with Endomat LC and Calcuson	1	pc	

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
8.7	Calcuson Probe For PCN			1	Unit	
		Ultrasonic Lithotripsy Probe	: Ultrasonic Lithotripsy Probe, without oscillating tip, with suction channel, ø 3.5 mm, length 40 cm, for use with HOPKINS Telescopes 27292 AMA/27293 AA and Sheaths 27293 BD/CD	3	pcs	
		Ultrasonic Lithotripsy Probe	: Ultrasonic Lithotripsy Probe, with ossillating tip and suction channel, ø 3.5 mm, length 40 cm, for use with HOPKINS Telescopes 27292 AMA/27293 AA and Sheaths 27293 BD/CD	3	pcs	
		Ultrasonic Lithotripsy Probe	: Ultrasonic Lithotripsy, Probe, without oscillating tip, with suction channel, ø 3 mm, length 40 cm, for use with HOPKINS Telescopes 27292 AMA/27293 AA and Sheaths 27294B	3	pcs	
		Ultrasonic Lithotripsy Probe	: Ultrasonic Lithotripsy Probe, with oscillating tip and suction channel, diameter 3 mm, length 40 cm for use with HOPKINS® Telescopes 27294 AA, 27295 AA, Operating Sheath 27294 B and Nephroscope for MIP L 27840 KA	3	pcs	
8.8	Calcuson Probe For Mini PCN			1	Unit	
		Ultrasonic Lithotripsy probe	: Ultrasonic Lithotripsy probe without oscillating tip, with suction channel, diameter 1.5mm , length 37cm, for use with nephroscope dor MIP M 27830KA			
9	OBGYN SURGICAL EQUIPMENT					
9.1	Hysterectomy Instrument Set			1	Set	
		SCALPEL HANDLE #3 125MM		1	pc	
		SCALPEL HANDLE #4 135MM		1	pc	
		MAYO-HARRINGTON SCISSORS CVD 230MM		1	pc	
		MAYO-STILLE SCISS BVLD-BLD STR 140MM		1	pc	
		MAYO-STILLE SCISS BVLD-BLD CVD 165MM		1	pc	
		NELSON-METZENBAUM SCISSORS CVD 250MM		1	pc	
		SIMS SCISSORS CVD S/B 200MM		1	pc	
		STANDARD FORCEPS SERR 145MM		2	pcs	

NO.	Item	Purchaser's Specifications	Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		STANDARD FORCEPS SERR 250MM	1	pc	
		STANDARD TISSUE FORCEPS 1X2 145MM	2	pcs	
		STANDARD TISSUE FORCEPS 1X2T.200MM	1	pc	
		RAMPLEY SPONGE FORCEPS STR SERR250MM	4	pcs	
		BACKHAUS TOWEL CLAMP 90MM	8	pcs	
		HALSTED-MOSQUITO FORCEPS DELSTR 125MM	6	pcs	
		HALSTED-MOSQUITO FORCEPS DEL CVD 125MM	6	pcs	
		CRILE FORCEPS CVD 140MM	6	pcs	
		SPENCER-WELLS FORCEPS CVD 150MM	6	pcs	
		KOCHER-OCHSNER FORCEPS STR 1X2 200MM	4	pcs	
		HEANEY HYST FORCEPS GROOVED 205MM	4	pcs	
		HEANEY HYST FORCEPS GROOVED 195MM	4	pcs	
		WERTHEIM-CULLEN CLAMP GROOVED 216MM	2	pcs	
		MAYO-HEGAR NEEDLE HOLDER 200MM	2	pcs	
		MASSON NDL HLDR HVY- SERRGROOVE 265MM	1	pc	
		ABDOMINAL RETRACTOR 48X90MM WIDE	1	pc	
		DOYEN ABDOMINAL RETRACTOR 48X105MM WIDE	1	pc	
		RIBBON RETRACTOR MALL 330X40MM	1	pc	
		BALFOUR ABDOMINAL RETRACTOR 200X235MM	1	pc	
		ALLIS FORCEPS 4X5 155MM	2	pcs	
		DUVACOLLIN INTESTINAL FORCEPS 195MM	2	pcs	
		DOYEN INTESTINAL FORCEPS CVD 240MM	2	pcs	
		DOYEN RETRACTOR 90X45MM 242MM	1	pc	
		DOYEN RETRACTOR 120X45MM 242MM	1	pc	
		SIMON VAGINAL RETR 115X26MM 273MM	1	pc	
		BOZEMANN FORCEPS S-CVD SERR 250MM	2	pcs	
		SCHROEDER TENACULUM FRCPSTD 1X1 250MM	2	pcs	
		SCHROEDER TENACULUM FRCPSTR2X2 250MM	1	pc	

NO.	Item	Purchaser's Specifications	Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		DOYEN MYOMA SCREW 150MM	1	pc	
		YANKAUER SUCTION CANNULA 2.0MM 285MM	1	pc	
		SINGLE USE PAPER FILTER WITH INDICATOR	1	pc	
		1/1 BASKET W/O STACK.FEET 540X253X64MM	1	pc	
		BOTTOM FOR 1/1 CONTAINER HEIGHT:135MM	1	pc	
		FULL-SIZE LID W/RETENTION PLATE SILVER	1	pc	
9.2	Sectio Caesarea Instruments		1	Set	
		MAIER FORCEPS W/RCHT CVD260MM	2	pcs	
		BACKHAUS TOWEL CLAMP 110MM	8	pcs	
		SCALPEL HANDLE #4 135MM	2	pcs	
		TC METZENBAUM SCISSORS CVD 200MM	1	pc	
		TC NELSON-METZ SCISSORS CVD 230MM	1	pc	
		TC SUTURE WAVECUT SCISSORS CVD 180MM	1	pc	
		TC MAYO-LEXER SCISSORS CVD 165MM	1	pc	
		TC SIMS UTERINE SCISS CVD B/B 200MM	1	pc	
		SURGICAL SCISSORS STR S/B 145MM	1	pc	
		TISSUE FORCEPS SERR 145MM	1	pc	
		TISSUE FORCEPS STR 1X2 145MM	2	pcs	
		STANDARD TISSUE FORCEPS 1X2T.200MM	2	pcs	
		DEBAKEY ATR.FCPS 2.0MM STR 150MM	2	pcs	
		DEBAKEY ATR.FCPS 2.0MM STR 200MM	2	pcs	
		ROCHESTER-OCHSNER FCPS STR 1X2140MM	6	pcs	
		PEAN FORCEPS STR 140MM	6	pcs	
		KOCHER-OCHSNER FORCEPS STR 1X2 200MM	6	pcs	
		ROCHESTER-PEAN FORCEPS STR 200MM	6	pcs	
		MAIER FORCEPS W/RCHT STR 260MM	4	pcs	
		MIKULICZ PERITONEUM FORCEPS CVD.200MM	6	pcs	
		FAURE PERITONEUM FORCEPS STRNG CVD 205MM	2	pcs	

NO.	Item	Purchaser's Specifications	Quantity	Statement of Compliance (Bidder's Offered Item & Specification)
		HEYWOOD-SMITH FORCEPS 210MM	2 pcs	
		RECAMIER SCOOP FIG 1 365MM	1 pc	
		FEMALE CATHETER METAL CHAR.12 160MM	1 pc	
		TC CRILE-WOOD NDL HLDR STR SERR 145MM	1 pc	
		TC MAYO-HEGAR NDL HOLDER HVY SERR 205MM	1 pc	
		TC HEGAR NEEDLE HOLDER HVY- SERR 205MM	1 pc	
		TC HEGAR NEEDLE HOLDER HVY- SERR 240MM	1 pc	
		ROUX RETRACTOR 3/SET 165MM	1 pc	
		VOLKMANN RETR6-PRG SEMI- S8.5X29 222MM	2 pcs	
		HABERER RIBBON RETRACTOR 50/40MM 305MM	1 pc	
		FRITSCH ABDOMINAL RETRACTOR 64X85MM #5	2 pcs	
		DOUBLE-ENDED PROBE 2.0MM 300MM	1 pc	
		INTERIOR BOX F/BL930	1 pc	
		NEEDLE CASE W/7 SECTIONS 150X90X10MM	1 pc	
		LABORATORY DISH 0.4 L	2 pcs	
		KIDNEY TRAY STAINLESS STEEL 250MM	1 pc	
		REDON SPIKE CH.12 SLIG.CVD.TRIANG.TIP	1 pc	
		REDON SPIKE CH.14 SLIG.CVD.TRIANG.TIP	1 pc	
		SINGLE USE PAPER FILTER WITH INDICATOR	1 pc	
		1/1 BASKET W/O STACK.FEET 540X253X64MM	1 pc	
		BOTTOM FOR 1/1 CONTAINER HEIGHT:135MM	1 pc	
		FULL-SIZE LID W/RETENTION PLATE RED	1 pc	
9.3	Basic Set Laparoscopy Hysteroscopy, Myomectomy & Chys		1 Unit	
		Trocar, size 11 mm (30103MP)	: Trocar, size 11 mm, color code:	2 pcs
			: green, consisting of: 30103 P Trocar only, with pyramidal tip 30103 H2 Cannula without valve, 10.5 cm 30103 M1 Multifunctional Valve with insufflation stop- cock, length	3 pcs
		Trocar, size 6 mm (30160MP)	: Trocar, size 6 mm, consisting of:	1 pc

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
			30160 P Trocar only, with pyramidal tip 30160 H2 Cannula without valve, with insufflation stop- cock, length 10.5 cm 30160 M1 Multifunctional Valve	1	pc	
		Cleaning Brush, 7 mm, 35 cm	: Cleaning Brush, length 35 cm, O.D. 7 mm	1	pc	
		Uterine Tenaculum Forceps, 22 cm	: Uterine Tenaculum Forceps, Length 22 cm	1	pc	
		Cleaning Brush, 50 cm, 11 mm	: Cleaning Brush, length: 50 cm, O.D. 11 mm	1	pc	
		Cleaning Brush, 11 mm, 35 cm	: Cleaning Brush, length 35 cm, O.D. 11 mm	1	pc	
		Instrument Oil, 50 ml	: Oil for Instruments, Bottle of 50ml	1	pc	
		VERESS Pneumoperitoneum Needle, 13 cm	: VERESS Pneumoperitoneum Needle, with spring-loaded blunt inner cannula, LUER-Lock, autoclavable, diameter 2.1 mm, length 13 cm	1	pc	
		Handle with Two-Way Stopcock	: Handle with Two-Way Stopcock for	1	pc	
			suction and irrigation, autoclavable, for use with suction and irrigation tubes size 5 mm	1	pc	
		Myoma Fixation Instrument	: Myoma Fixation Instrument, screw shaped, ø 5 mm	1	pc	
		Palpation Probe, with cm-markings	: Palpation Probe, with cm marking, size 5mm, length 36 cm	1	pc	
		Puncture Needle, dia. 1.6 mm, 36 cm	: Puncture Needle, LUER-lock, diameter 1.6 mm, size 5 mm, length 36 cm,	1	pc	
		Injection Needle, dia.	: Injection Needle, LUER-lock, diameter 1.2 mm, size 5 mm, length 36 cm.	1	pc	
		Cleaning agent, tube 5 gr.	: Cleaning agent for distal and proximal lenses and fiber optic surfaces of endoscopes,tube 5 gr.	1	pc	
		Special Lubricant for Stopcocks	: Special lubricant for stopcocks	1	pc	
		Suction a. Irrig. Cannula,L. 36cm	: Suction and Irrigation Cannula with lateral holes, size 5 mm, length 36 cm, for use with suction and irrigation handles	1	pc	
		Spare Needle, Ø 0.7 mm, 31 cm	: Replacement Needle, diameter 0.7 mm, length 31 cm, for use with 30675 ND	1	pc	
		MANHES High Frequency Needle	: MANHES High Frequency Needle, for splitting and coagulation, insulated with connector pin for unipolar coagulation, size 5 mm, length 31 cm	1	pc	

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		Coagulating and Dissecting Electrode, L Hook	: Coagulating and Dissecting Electrode, L-shaped, with connector pin for unipolar coagulation, size 5 mm, working length 36 cm	1	pc	
		Coagulating and Dissecting Electrode, Spatula 0804310417 AKS : 42000000-AKS- 000066179	: Coagulating and Dissecting Electrode, spatula-shaped, blunt with connector pin for unipolar coagulation, size 5 mm, working length 36 cm	1	pc	
		Reducer, 11/5 mm	: Reducer, 11/5 mm	1	pc	
		Bipolar High Frequency Cord, length 300 cm	: Bipolar High Frequency Cord, length 300 cm, for AUTOCON® II 400 SCB system (111, 113, 115, 122, 125), AUTOCON® II 200, AUTOCON® II 80, Coagulator 26021 B/C/D, 860021 B/C/D, 27810 B/C/D, 28810 B/C/D, AUTOCON® series (50, 200, 350), Erbe-Coagulator, T and ICC series, length 300 cm	1	pc	
		Unipolar High Frequency Cord, 300 cm	: Unipolar High Frequency Cord, with 5 mm plug, length 300 cm, for use with AUTOCON® II 400 SCB system (111, 115, 122, 125), AUTOCON® II 200, AUTOCON® II 80, KARL STORZ AUTOCON® system (50, 200, 350) and Erbe type ICC	1	pc	
		HOPKINS® II Telescope 0°, ICG, Ø 10mm	: HOPKINS® Straight Forward Telescope 0°, enlarged view, diameter 10 mm, length 31 cm, autoclavable, for indocyanine green (ICG) and autofluorescence (AF), fiber optic light transmission incorporated, for use with Fluid Light Cable 495 FQ/FR and Cold Light Fountain D-LIGHT P SCB 20133701-1, color code: green	1	pc	
		Fluid Light Cable, 250cm, ø5mm	: Fluid Light Cable, diameter 5 mm, length 250 cm	1	pc	
		CLICKLINE Metal Handle with MANHES style ratchet	: Metal Handle, with MANHES style ratchet	1	pc	
		CLICKLINE Plastic Handle	: Plastic Handle, without ratchet with connector pin for unipolar coagulation	1	pc	
		Metal Outer Sheath, insulated, 36 cm	: Insulated Metal Outer Tube, with LUER-Lock connector, size 5 mm, length 36 cm	1	pc	
		CLICKLINE Forceps Insert Claw Forceps, 2 x 3 teeth	: CLICKLINE Forceps Insert, Claw Forceps, 2 x 3 teeth, single action jaws, size 5 mm, length 36 cm	1	pc	

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		CLICKLINE Forceps Insert jaws with multiple teeth, width of jaws 4.8 mm	: CLICKLINE Forceps Insert, MANHES Grasping Forceps, jaws with multiple teeth, width of jaws 4.8 mm, for atraumatic and accurate grasping single action jaws, size 5 mm, length 36 cm	1	pc	
		CLICKLINE Forceps Insert Bowel Grasper, fenestrated, double action jaws	: CLICKLINE Forceps Insert, Bowel Grasper, fenestrated, double action jaws, size 5 mm, length 36 cm	1	pc	
		Forceps Insert "Cobra- Jaws", 1 x 2 teeth	: CLICKLINE Forceps Insert, MANHES Grasping Forceps, "Cobra-Jaws", 1 x 2 teeth, single action jaws, size 5 mm, length 36 cm	1	pc	
		CLICKLINE Forceps Insert KELLY Dissecting and Grasping Forceps long	: CLICKLINE Forceps Insert, KELLY Dissecting and Grasping Forceps long, double action jaws, size 5 mm, length 36 cm	1	pc	
		CLICKLINE Forceps Insert double action jaws, size 5 mm, length 36 cm	: CLICKLINE Forceps Insert, Grasping Forceps, double action jaws, size 5 mm, length 36 cm	1	pc	
		CLICKLINE Scissors Insert double action jaws	: CLICKLINE Scissors Insert, for scissors, double action jaws, serrated jaws, spoon-shaped, size 5 mm, length 36 cm, for use with trocars size 6 mm	1	pc	
		CLICKLINE Scissors Insert Hook Scissors	: CLICKLINE Scissors Insert, Hook Scissors, single action jaws, size 5 mm, length 36 cm	1	pc	
		HOPKINS® Telescope 30°, 10 mm, 31 cm	: HOPKINS® Forward-Oblique Telescope 30°, enlarged view, diameter 10 mm, length 31 cm, autoclavable, fiber optic light transmission incorporated, color code: red	1	pc	
		RoBi® Metal Outer Sheath length 36 cm	: RoBi® Metal Outer Sheath, insulated, with LUER-Lock connector for cleaning, size 5 mm, length 36 cm	1	pc	
		RoBi® KELLY Forceps Insert, CLERMONT-FERRAND model, length 36 cm	: RoBi® KELLY Forceps Insert, long, CLERMONT-FERRAND model, especially suitable for dissection, double action jaws, size 5 mm, length 36 cm, color code: light blue	1	pc	
		RoBi® KELLY Forceps Insert	: RoBi® KELLY Forceps Insert, CLERMONT-FERRAND model, especially suitable for dissection, double action jaws, size 5 mm, length 36 cm, color code: light blue	1	pc	

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		Knot Tier, 5 mm, 36 cm	: KÖCKERLING Knot Tier, size 5 mm, working length 36 cm, for extracorporeal knotting	1	pc	
10	NEURO-INTERVENTION CENTER EQUIPMENT					
10.1	Transcranial Magnetic Stimulation			1	Unit	
		Main Unit				
		Main unit is the basis of any configuration. The main stimulator unit is intended for stimulator operation control and can be used as an independent device (if it is equipped with coils). The front panel contains digital indicators displaying all parameters of stimulator operation and controls used to adjust stimulation parameters.				
		Cooling Unit				
		One of the problems of magnetic stimulator application is quick overheating of coil during the stimulation performing. In Neuro-MS/D this problem is solved with the use of special cooling unit and cooled coils. In fact, this is a tank with the cooling liquid, the pump running the cooling liquid through the coil and the fridge. The Unit allows increasing continuous operation time up to 10 000 pulses without overheating. Actually, it means that stimulator can operate for a long time without overheating.				
		Extra Power Supply Unit				

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		<p>The main unit of the magnetic stimulator allows operating with up to 30Hz frequency. However, the stimulator does not generate the maximal induction at 30 Hz frequency. It can be achieved only at 5 Hz (or less) frequency. Also there is a term "maximal effective stimulation frequency". This term indicates the frequency at which transcranial magnetic stimulation can be performed and each pulse in series is higher than motor threshold for most people. For main unit equals 10 Hz. The extra power supply unit makes it possible to increase this frequency twice (up to 20 Hz)</p>				
		Neuro-MS.NET Software				
		<p>The delivery set includes the special software for magnetic stimulator control with the use of computer. This software allows keeping the patient database, detecting motor threshold, controlling the stimulation courses and sessions. A user can perform the stimulation according to already specified stimulation programs and also create own ones or edit the available stimulation programs.</p>				
		Advanced Therapeutic Principle				

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		<p>The principle of therapeutic magnetic stimulation is based on the following. The magnetic stimulator uses the magnetic pulses of short duration and emerging high intensity electromagnetic field easily penetrates through clothes, cranium. The distinctive feature of Neuro-MS/D device is influence upon deep nerve centers, peripheral nerves, cerebral and spinal cord, which are inaccessible for other kinds of stimulation, bones and soft tissues. They exert possibility to perform transcranial magnetic stimulation (TMS). However, the well-known problem is quick coil overheating.</p>				
		<p>The cooling unit included in therapeutic delivery set variant allows performing long-term therapeutic impacts (also transcranial magnetic stimulation with high frequency and intensity) without coil overheating.</p>				
		<p>Advanced Therapeutic Variant provides</p>				
		<p>the possibility to increase the so called maximal effective stimulation frequency (the frequency when each stimulus in series has 100% intensity of motor threshold for most people) twice (up to 20 Hz) owing to extra power supply unit.</p>				
		<p>Most often these stimulator variants are used to treat depressions (including severe and drug-resistant), tinnitus. Besides, there are positive and encouraging results obtained at rehabilitation of stroke patients.</p>				
		<p>Neuro-MS/D (Therapeutic) Applications: Neurology:</p>				

NO.	Item	Purchaser's Specifications	Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		* treatment of central and peripheral nervous system disorders: vascular and vertegenic pathologies, consequences of stroke, neuropathies, demyelinating disorders of nervous system, spinocerebellar degeneration, spasticity, pain syndrome, radiculopathies, hemicrania, Alzheimer's disease.			
		Ophthalmology:			
		* partial atrophy of visual nerve owing to different etiology.			
		Psychiatry:			
		* treatment of depressions, schizophrenia, obsessive-compulsive disorders, manias and other psychiatric disorders. The delivery set of therapeutic variant includes Neuro-MS.NET software allowing to program any stimulation algorithms. It also provides theta-burst mode with up to 100 Hz stimulation frequency.			
		In case the therapeutic variant is equipped with neurophysiological equipment, it will receive all capabilities of diagnostic variant.			
		2 Channel Portable Digital Neuro MEP Micro System			
		Amplifiers:			
		Sampling rate per channel			
		A/D converter			
		Sensitivity			
		Input impedance			
		Noise level in the band			
		High pass filter			
		Low pass filter			
		Common mode rejection			
		Interface			
		Electrical Stimulator:			
		Stimulus amplitude			
		Stimulus duration			
		Visual Stimulator:			
		Stimulus amplitude			
		Stimulation frequency			
		Auditory Stimulator:			
		Stimulus intensity			
		Stimulus frequency			

NO.	Item	Purchaser's Specifications	Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		Pattern Stimulator:			
		Stimulation frequency			
		EMG Menu:			
		Surface EMG (spontaneous activity, interference curve) Stimulation EMG (motor end sensory nerve conduction study, F-wave, H-reflex (also including paired stimulation) T-reflex, blink reflex, magnetic stimulation			
		Rhythmical stimulation (decrement-test) (Impulse series stimulation by user-defined algorithm, tetanization)			
		Needle (local) EMG spontaneous activity interference curve, motor unit potentials (jitter)			
		Somatosensory evoked potentials (SEP)			
		Standart Delivery:			
		Main Unit	1	Unit	
		Cooling Unit	1	Unit	
		Extra Power Supply	1	Unit	
		Cooled Angulated figure-of-eight Coil	1	pc	
		Big Ring Coil	1	pc	
		End Cap	1	pc	
		Techmat Manual	1	Set	
		User Manual	1	Set	
		ITBS - CTBS software	1	Unit	
		Coil Holder	1	pc	
		2 - Channel digital SEP system including master and software	1	Unit	
		Laptop	1	Unit	
		Local Trolley	1	Unit	
		IDA Stabilizer	1	Unit	
11	EYE CENTER EQUIPMENT				
11.1	YAG III Laser		1	Unit	
		Photodistruption Laser			
		Laser System			
		Mode			: Super-Gaussian
		Wave Length			: 1064 nm
		Optical Breakdown			: Typically 2.5 mJ in the air
		Pulse Length			: < 4 ns (Typically 2-3 ns)
		Max. Laser Energy			: Single Pulse; typically 10 mJ
					Double Pulse; typically 23 mJ
					Triple Pulse; typically 35 mJ
		Energy Attenuation			: 22 levels

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		Pulse Repetition Frequency	: Max. 2.5 Hz			
		Focus Diameter	: 10 um in air			
		Exit Aperture Angle	: 16°			
		Aiming Beam :	: Diode approx. 670 nm, power 5 uW - 150 uW; 4-point aiming beam			
		Focusing Shift	focusing system			
		Laser Slit Lamp	: Variable: +150 um; 0; -150um			
		Magnification	: 5/ 8/ 12/ 20/ 32 x			
		Illumination	: 12 V, 30 W, brightness continuously adjustable			
		Slit Length	: Variable in steps of 1/3/5/9/14 mm			
		Slit Width	: Continuously adjustable from 0-14 mm			
		Slit Image Rotation	: 0°, ±45°, 90°			
		Physician Safety Filter	: Color Fidelity			
		Dimensions (L x W x H)	: 40 x 35 x 62.3 (cm)			
		Weight	: 11 kg			
		Electrical and Physical Data of Laser Console				
		Weight	: 4 kg			
		Dimensions (L x W x H)	: 33 x 21 x 13.5 (cm)			
		Electrical Rating (230 V)	: 100- 240 V, 50/60 Hz			
11.2	OCT (Optical Coherence Tomograph)	Basic Component		1	Unit	
			1. Laser scanning camera			
			2. Camera mount with integrated headrest			
			3. 30° Lens			
			4. Power supply / laser box (PSW PS410 or PWS/FW)			
			5. Cable connecting Control Panel and power supply			
			6. Power Supply Model PWS / Thunderbolt 2 cable to PC			
			7. CD containing operation software			
			8. Software protector (Dongle) 1 fix + 2 Floating Licences			
			9. Operation Manuals			
			- Hardware Operation Instructions (this document)			
			- Software Operation Instructions (Spectralis QuickGuide)			
			- Manual "Installation and System Configuration"			
			10. Heidelberg Table for OCT			

NO.	Item	Purchaser's Specifications	Quantity	Statement of Compliance (Bidder's Offered Item & Specification)
		11. PC + Monitor + Printer (Local)		
		12. Touch Screen Panel		
		13. Foot Switch		
		14. Anterior Segment Lens		
	Focus Adjustment range	15. Wide Field Lens 55°		
	OCT Imaging			
	- Methodology	-12 diopters to +12 diopters spherical		
	- Light Source SD OCT			
		Spectral Domain OCT		
		Super Luminescence Diode (SLD) center wavelength 870nm,		
	Fundus Imaging	Class 1 laser conduct		
	- Methodology	Confocal Scanning Laser Ophthalmoscope (cSLO)		
	- Fundus Image	Simultaneous Dual Beam Scanning		
	- Light Source IR	Laser, wavelength 815 nm, Class 1 laser product		
	- Field of View (W x H)	300 x 300		
	- Isotropic Resolutions	5 µm High Resolution Mode		
	Retinal Tracking	11 µm High Speed Mode		
		TruTrack TM Active Eye Tracking		
	Module	1. ART (Automatic Real Time) image Stabilization		
		2. True Track Active Eye Tracking		
		3. Infrared : Diode Laser 830nm		
		4. Red Free : Argon Laser 514nm		
		5. SD-OCT		
		6. Full Deep Imaging (FDI)		
		7. Transverse (En Face) OCT		
		8. Neurology		
		9. 4D - Time		
		10. Blue Peak Autofluorescence		
		11. Multicolor		
		12. Glaucoma Premium Software		
		13. Anterior Segment Module		
	OCT Scanner Specifications	A-Scans		
		Scan rate: 85,000 Hz		
		Scan depth: 1.8 mm		

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
			Scan size: 512 pixels			
			Axial resolution: 7 µm optical			
			3.5 µm/pixel digital			
			Lateral resolution: 14 µm optical			
			B-Scans			
			Scan angle: 55 / 35 / 25 degrees			
			Scan width: up to 9 mm			
			High speed mode			
			Scan width: 768 A-Scans			
			Acquisition time: 19 ms / B-Scan			
			Lateral resolution: 11 µm/pixel digital			
			Scan rate: 48 B-Scans/sec			
		OCT Scanner Specification	High resolution mode			
			Scan width: 1,536 A-Scans			
			Acquisition time: 38 ms / B-Scan			
			Lateral resolution: 6 µm/pixel digital			
			Scan rate: 25 B-Scans/sec			
		Scanning Laser Specifications	Transversal field of view			
		(55°/ 35°/ 25°)	Scan angle: 55°x55°, 35°x35°, 25°x25°, 30°x30°, 20°x20°, 15°x15°,			
		(30°/ 20°/ 15°)	Wide field composite image to 150°			
			High speed mode			
			Digital image size: 768x768 / 512x512 / 384x384.			
			Scan time per image: 96ms / 64 ms / 48 ms			
			Lateral resolution 10 µm/pixel digital			
			Image Acquisition Frequency 9 Hz / 12.5 Hz / 16 Hz			
			High resolution mode			
			Digital image size: 1536x1536 / 1024x1024 / 768x768			
			Scan time per image: 192 ms / 128 ms / 96ms.			
			Lateral resolution 5 µm/pixel digital			
			Image Acquisition Frequency 5 Hz / 7 Hz / 9 Hz			
			Maximum Scan Depth			

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
			8 mm			
		OCT Angiography Specifications	Algorithm : Amplitude decorrelation			
			Light source : 870nm			
			Scan rate : 85,000 Hz			
			Scan depth: 1.8 mm			
			Scan size: 512 pixels			
			Scan Angle : 10° x 10°, 15° x 15° and 30° x 15°			
			Axial resolution: 3.9 µm / pixel			
			Lateral resolution : 5.7 µm/pixel digital for 10° x 10°			
			Lateral resolution : 11 µm/pixel digital for 15° x 15°, 30° x 15°			
			Tracking system : True-Track™			
			Transverse resolution : 14µm			
			Combination with FA/ICGA : Possible			
			Scan Layers			
			- Vitreoretinal Interface			
			- Supervicial Vascular Complex			
			- NFL Vascular Complex			
			- Superficial Vascular Plexus			
			- Deep Vascular Complex			
			- Intermediate Capillary Plexus			
			- Deep Capillary Plexus			
			- Avascular Complex			
			- Choroicapillaries			
			- Choroid			
			Manual Segmentation Change			
			Artifact Removal			
		Focus Adjustment Range	- 12 diopters to +12 diopters spherical			
12	SIMULATION CENTER EQUIPMENT					
12.1	Male Catheterization Simulator	Male Catheterization Simulator: System to include: hard carry case, lubricant, silicone catheter, and instruction manual. Fluid supply stand not included. Packing size: approx. 17 in. x 12 in. x 10 in.		1	Unit	

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
12.2	Female Catheterization Simulator2	Female Catheterization Simulator2 to include: hard carry case, lubricant, catheter, and teaching guide. Fluid supply stand not included. Packing size: approx 24 in. x 16 in. x 13 in..		1	Unit	
		*NOTE: A Fr. Silicone Foley catheter can be used if extreme care is taken to inflate the cuff only when it is in the proper position. Just as in a real patient, the cuff must be completely deflated before the catheter is removed. Improper use of a Foley can result in damage to the simulator, just as when using a Foley catheter with a real patient.				
12.3	Intramuscular Injection Simulator	Intramuscular Injection Simulator to include: teaching guide, supply of syringes, and hard carrying case. Five-year warranty. Packing size: approx. 22 in. x 16 in. x 10 in.		2	Unit	
12.4	Simulator Intravenous Arm II	Set Includes:		2	Unit	
		2 Arm models with supporter stand				
		2 Injection pads				
		2 Injection pads (red)				
		1 Circulation pump				
		1 Jar of coloring powder (red)				
		1 Set of spoon and plastic jar				
		1 Intruccion manual				
		Replacement Part:				
		2 Replacement injection pad				
		2 Replacement injection pad (red)				
		Manikin Size:				
		approx. W54xD11xH11 cm				
		Features :				
		2 kinds of puncture pads for culty variation				
		3 accessible venous lines at cubital fossa:				
		Realistic needle tip resistance of vein walls				
		"Flask-back" can be observed	basilic, median and cephalic			
12.5	Suture and Stapling Practice Arm	Made with a soft vinyl skin over a core of stitchable foam		2	Unit	

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		Realistic skin texture with wrinkles, pores, and visible fingerprints. Soft and pliable for easy sewing, the skin is tough enough that sutures will not pull out when tightened.				
		The unit is provided with three wounds. These wounds can be sutured repeatedly until the skin around them is finally worn out, then, new wounds can be cut.				
		Although disposable, the arm provides hundreds of suturing experiences before wearing out.				
		Conservatively, over one hundred cuts can be made on the trainer and each of these cuts can be sutured several times.				
		Comes complete with a starter package of sutures and instruction booklet.				
12.6	Lumbar Puncture Simulator	The ultrasound lumbar puncture simulator is a trainer that includes the lumbar vertebrae, iliac crest, spinous process, ligamentum flavum, the epidural space and dura; gluteal fold and a fluid filled compartment for simulated cerebrospinal fluid. It comes to you with normal tissue and a simulated IV bag.		1	Unit	
		Skill Development				
		Practice lumbar puncture (spinal tap)				
		Practice spinal and epidural injections				
		Use ultrasound				
		Features				
		Fluid can be added to tissue				
		Durable tissue for multiple procedures				
		Position on its side (lateral decubitis positioning) or upright (sitting)				
		Components				

NO.	Item	Purchaser's Specifications	Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		Lumbar Puncture/Epidural Trainer body form, Replaceable Tissue, Simulated IV Bag (IVB-20), and Syringe			
		Dimensions			
		Size: approx. 9" x 13" x 14"			
		Weight: approx. 16 lbs			
12.7	Perineal Repair Trainer	The Perineal Repair Trainer is the only soft tissue model for anatomical and procedural training of first to fourth degree perineal tears.	1	Unit	
		The trainer includes vaginal and anal canals, rectovaginal fascia, skin and muscle layers, a retractable rectal sphincter and rectal mucosa; and allows for midline, mediolateral, and lateral incisions.			
		The replaceable tissue allows for multiple cuts and realistic suturing of the vaginal mucosa, muscle and subcutaneous layers.			
		The tray overlays the tissue providing tension that enhances the simulation and creates a bony anatomical landmark simulating the ischial spine that allows the user to perform a pudendal block.			
		The internal distension rod provides more realistic access to deeper tissues during 3rd and 4rd degree repairs.			
		Skill Development			
		Incision training for midline, mediolateral and lateral incisions			
		Retract the tissue with non-dominant hand			
		Insertion of vaginal (or any) retractor			
		Suture tissue layers			
		-perform a 1st to 4th degree repair			
		Features			
		Replaceable tissue allows for multiple incision sites and suturing			
		Most realistic tissue properties for training 4th degree repair with a retractable sphincter and rectal mucosa			

NO.	Item	Purchaser's Specifications	Quantity	Statement of Compliance (Bidder's Offered Item & Specification)
		Adjustable tension		
		Base sits securely to table		
		External and Internal Anatomy		
		Vaginal and anal canals		
		Vaginal mucosa		
		Rectovaginal fascia		
		Transverse perineal muscle		
		External anal sphincter - enabling end to end repair		
		Ischial spine for performing pudendal nerve block		
		Components		
		Perineal Repair Trainer Base		
		Tension Rod		
		Perineal Repair Replacement Tissue (PRTT-20)		
		Dimensions		
		Size: approx. 9" h; 10" w; 7.5" d		
		Weight: approx 6 lbs.		
12.8	Child Airway Management Trainer with Stand	A simulated head of an 5-year-old child featuring realistic size and anatomy.	1 Unit	
		Perfect for practicing airway management skills on pediatric patients.		
		Realistic anatomy includes mouth, tongue, oral pharynx, larynx, epiglottis, vocal cords, trachea, and esophagus.		
		Separate lungs for auscultation. Inflatable stomach bladder indicates esophageal insufflation.		
		Practice suctioning and oral, nasal, and intubation techniques.		
		Includes training stand to mount head, pump spray lubricant, and hard carrying case. Manual carotid pulse.		
12.9	Prostate and Rectal Exam	The Prostate Examination Simulator is an indispensable model for both students and professionals.	1 Unit	
		Instructors have the ability to teach techniques of prostate examination with no harm or embarrassment to real patients.		

NO.	Item	Purchaser's Specifications	Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		Four separate prostate glands are supplied with the torso, representing one benign gland and three stages of prostatic carcinoma in varying degrees of development.			
		Each gland can be inserted into the prostate torso to allow realistic practice in diagnosis by rectal palpation.			
		STAGE A GLAND - Benign, slightly enlarged, but otherwise normal prostate gland.			
		STAGE B GLAND - A discrete, hard nodule is palpable in the upper right quadrant. This simulates a beginning stage of carcinoma.			
		STAGE C GLAND - The spread of carcinoma is demonstrated in this gland. The small nodule has increased in size and has become an external hard mass on the surface of the gland.			
		STAGE D GLAND - This gland is totally replaced with carcinoma. The entire gland will feel hard and irregular.			
		Life/form® Prostate Examination Simulator is complete with four glands, hard carrying case, lubricant, and teaching guide. Five-year warranty. Size: 22 in. W x 15 in. D x 12 in. H.			
12.10	Eye Examination Simulator	Set Includes:	1	Unit	
		1 Manikin head and shoulder			
		- 3 Steps (2,3,5,5 mm diameter)			
		- 1 Slide holder with 3 steps depth setting			
		1 Instruction manual			
		1 Set of case slides			
		1 Slide cluster			
		1 Storage case			
		Replacement part			
		1 Replacement fundus case slides (set of 10 cases)			
		Manikin Size			
		approx W42xD22XH38 cm			
		Features :			

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		1. 10 Cases of fundus slides are provided for training in identifying common eye disease				
		2. The slides images are from actual clinical images				
		3. The lens-equipped eyeball unit reproduce the visual axis close to that of the human eye providing a realistic eye-ground view				
		4. Soft and supple material of the manikin allows hands-on practice of the examination procedures, such as raising the eyelid				
		5. The depth of the fundus slides can be set 3 levels; hyperopic, normal, and myopic views				
		6. Red Reflection can be simulated				
13	REHABILITATION CENTER EQUIPMENT					
13.1	High Level Laser Therapy	Main Power	: 100 - 240V/50-60Hz	1	Unit	
		Electrical Safety Class	: Directive 93/42 Classification IIb			
		Pulse width	: 1-1000 ms			
		IP class	: IPX0 device, IPX0 hand piece, IPX4 pneumatic footswitch			
		Dimensions	: approx 390 x 250 x 170 mm			
		Weight	: approx 3,8 kg			
		Wavelength HPL 7	: 810 nm + 980 nm			
		Guide Light	: 650 nm - 3 mW			
		Laser Power	: up to 7 W Continuous (CW), Pulsed, Single Pulse, Burst			
		Emission and Stochastic (patented stochastic mode)	: max. 450 VA			
		Operation Mode	: Continuous, Pulsed, Single Pulse, Burst, Stochastic and Anti-Inflammation			
		Pathologies	: Over 60 pathologies with interactive illustrations and protocols subdivided by phase			
		Programmable	: 12 positions by name			
		Calibration	: Graphic and acoustic control system for laser emission at hand piece exit in accordance with norm CEI EN 60825-1			
		Display	: Color TFT 7" Touch – screen			
		Absorption Power	: 160 VA			
		Laser Class	: IV			
		Beam Divergence	: 25°			

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		Terms Operating	: 0 - 30°C, 30 - 75% humidity noncondensing 700 - 1060 hPa			
		Terms Transportation and Storage	: -10 - 60°C, 10 - 100% humidity noncondensing 500 - 1060 hPa			
		DNRO	:Nominal Distance of Ocular Risk 2.4m			
		Conformity	:EN 60601-1; EN 60601-1-2; IEC 60601-2-22			
		Applicator 26mm				
		Applicator 36mm				
		Laser handpiece		1	pc	
		Safety footswitch		1	pc	
		Safety glasses		1	pc	
		3 Pole interlock plug		1	pc	
		Multilingual manual on USB		1	pc	
		Power cord		1	pc	
		Features:				
		1. Deep tissue penetration with power up to 7 W				
		2. Optimal tissue absorption due to the 2 or 3 different wavelengths: 810 nm, 980 nm				
		3. Preset protocols for easy application				
		4. Large touch screen, 7 inch with an optimal interface flow				
		5. Automatic laser source calibration				
		6. Safety footswitch operation				
		7. Different emission modes for optimal output adjustment (Continuous, Pulsed, Single Pulse, Burst, Stochastic and Anti- Inflammation)				
13.2	Ultrasound Diathermy			1	Unit	
		• 1 and 3 MHz Ultrasound Frequencies				
		• Pulsed and Continuous Ultrasound therapy operation (10%, 20%, 50%, 100%)				
		• Variable duty cycle outputs of 16 Hz, 48 Hz, or 100 Hz for ultrasound				
		in variety of sizes (1 cm²,2 cm²,5 cm²,10cm²)				
		Main Power	: 120-240 VAC, 50-60 Hz			
		Weight approx.	: 2.3 kg			

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		Dimensions approx.	: 33x29x16,3 cm			
		Consisting of:				
		5 cm Applicator		1	pc	
		Ultrasound Gel		1	pc	
		User Manual on CD		1	pc	
		Cable Power Cord		1	pc	
		Extraction screw, conical for screws ø2.7, 3.5 and 4.0 mm		2	pcs	
		Extraction screw, for screws ø3.5mm		2	pcs	
		Handle with Mini Quick Coupling		1	pc	
		T-Handle with Mini Quick Coupling		1	pc	
		Screwdriver Shaft Stardrive @1.3, Short, Self-Holding for Mini Quick Coupling		1	pc	
		Screwdriver Shaft Stardrive @1.5, Short, Self-Holding for Mini Quick Coupling		1	pc	
		Screwdriver Shaft Stardrive @2.0, Short, Self-Holding for Mini Quick Coupling		1	pc	
		Screwdriver Shaft Stardrive @2.4, Short, Self-Holding for Mini Quick Coupling		1	pc	
		Holding Sleeve for Mini Screws, for Nos. 314.300 and 314.320		1	pc	
		Screwdriver Shaft 1.0, Cruciform, Self-Holding, for Mini Quick Coupling		1	pc	
		Screwdriver Shaft 1.3, Cruciform, Self-Holding,		1	pc	
		Screwdriver Shaft 1.52.0 Cruciform,self -holding		1	pc	
		Screwdriver Shaft, Hexagonal small, ø 2.5 mm		1	pc	
		Screwdriver Shaft, Hexagonal for screws ø 1.5 mm and 2.0 mm		1	pc	
		Vario Case™ Framing with Bottom, Size 1/2, height 88 mm		1	pc	
		Lid (stainless steel), Size 1/2, for Vario Case		1	pc	
		Extraction Module for screw ø 3.5, 4.0 and 4.5 mm		1	Unit	
		Which consists of :				
		Screwdriver Shaft 1.0, T25, Length 100mm		1	pc	
		Hollow Reamer, complete, anticlockwise cutting, for screws ø 3.5 mm and 4.0 mm		1	pc	

NO.	Item	Purchaser's Specifications	Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		Hollow Reamer, complete, anticlockwise cutting, for screws ø 4.5 mm	1	pc	
		Spare Reamer Tube, for No.309.035	1	pc	
		Spare Reamer Tube, for No.309.450	1	pc	
		Extraction Bolt, for screws ø 3.5 mm and 4.0 mm	1	pc	
		Extraction Bolt, for screws ø 4.5 mm and 5.0 mm	1	pc	
		Extraction screw, conical, for screws ø 2.7, 3.5, and 4.0 mm	1	pc	
		Extraction screw for screws ø 3.5 mm	1	pc	
		Extraction screw, conical for screws ø 4.5 mm and 6.5 mm	2	pcs	
		T-Handle with Quick Coupling	1	pc	
		Screwdriver Shaft, hexagonal, small, Ø 2.5 mm	1	pc	
		Screwdriver Shaft Stardrive® 3.5, T15, self-holding, for AO/ASIF Quick Coupling	1	pc	
		Screwdriver Shaft, hexagonal, large, Ø 3.5 mm	1	pc	
		Vario Case™. Framing with Bottom, size 1/2, height 88 mm	1	pc	
		Lid (stainless steel), size 1/2, for Vario Case™	1	pc	
		Extraction Module for Screws Ø 5.0, 6.0, 6.5, 7.0 and 7.3 m	1	Unit	
		Which consists of:			
		Screwdriver Shaft, hexagonal, hexagonal head 4 mm, length 100 mm	1	pc	
		Screwdriver Shaft, T25, length 100 mm	1	pc	
		Screwdriver Shaft, T40, length 100 m	1	pc	
		Screwdriver Shaft, hexagonal, large, Ø 3.5 mm	1	pc	
		Hollow Reamer, complete, anticlockwise cutting, for Screws Ø 5.0, 6.0, 6.5 and 7.0 mm	1	pc	
		Hollow Reamer, complete, anticlockwise cutting, for Screws Ø 4.5 mm	1	pc	
		Spare Reamer Tube, for No. 309.065	1	pc	
		Spare Reamer Tube, for No. 309.450	1	pc	
		Extraction Bolt, for Screws Ø 6.0, 6.5 and 7.0 mm	1	pc	

NO.	Item	Purchaser's Specifications	Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		Extraction Bolt, for Screws Ø 4.5 and 5.0 mm	1	pc	
		Extraction Screw, conical, for Screws Ø 2.7, 3.5 and 4.0 mm	1	pc	
		Extraction Screw for Screws Ø 3.5 mm	1	pc	
		Extraction Screw, conical, for Screws Ø 4.5 and 6.5 mm	2	pcs	
		T-Handle with Quick Coupling	1	pc	
		Vario Case™, Framing with Bottom, size 1/2, height 88 mm	1	pc	
		Lid (stainless steel), size 1/2, for Vario Case™	1	pc	
		HSS Drill Bit			
		HSS Drill Bit Ø 2.5 mm for Implant Steel, sterile	2	pcs	
		HSS Drill Bit Ø 3.5 mm for Implant Steel, sterile	2	pcs	
		HSS Drill Bit Ø 4.8 mm for Implant Steel, sterile	2	pcs	
		CARBIDE Drill Bit			
		Carbide Drill Bit Ø 4.0 mm for Instrument Steel and Titanium, sterile	2	pcs	
		Carbide Drill Bit Ø 6.0 mm for Instrument Steel and Titanium, sterile	2	pcs	
14	ORTHOPAEDIC AND TRAUMATOLOGY EQUIPMENT				
14.1	Removed Damages Screw		1	Set	
		Extraction Module for screw ø 1.0, 1.3, 1.5, 2.0, 2.4, 2.7 and 3.0 mm			
		Which consists of:			
		Screwdriver shaft, cruciform 2.4 length 100 mm	1	pc	
		Spare Reamer Tube for No. 309.150	1	pc	
		Spare Reamer Tube for No. 309.200	1	pc	
		Spare Reamer Tube for No. 309.250	1	pc	
		Extraction Bolt for screws ø 1.5 mm	1	pc	
		Extraction Bolt for screws ø 2.0 mm	1	pc	
		Extraction Bolt for screws ø 2.7 mm	1	pc	
		Hollow Reamer, Complete, anticlockwise cutting for screws ø1.5 mm	1	pc	

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		Hollow Reamer, Complete, anticlockwise cutting for screws ø 2.0mm		1	pc	
		Hollow Reamer, Complete, anticlockwise cutting for screws ø 2.7 mm		1	pc	
		Extraction screw, conical for screws ø 1.5 mm and 2.0 mm		2	pcs	
		Extraction screw, conical for screws ø2.7, 3.5 and 4.0 mm		2	pcs	
		Extraction screw, for screws ø3.5mm		2	pcs	
		Handle with Mini Quick Coupling		1	pc	
		T-Handle with Mini Quick Coupling		1	pc	
		Screwdriver Shaft Stardrive @1.3, Short, Self-Holding for Mini Quick Coupling		1	pc	
		Screwdriver Shaft Stardrive @1.5, Short, Self-Holding for Mini Quick Coupling		1	pc	
		Screwdriver Shaft Stardrive @2.0, Short, Self-Holding for Mini Quick Coupling		1	pc	
		Screwdriver Shaft Stardrive @2.4, Short, Self-Holding for Mini Quick Coupling		1	pc	
		Holding Sleeve for Mini Screws, for Nos. 314.300 and 314.320		1	pc	
		Screwdriver Shaft 1.0, Cruciform, Self-Holding, for Mini Quick Coupling		1	pc	
		Screwdriver Shaft 1.3, Cruciform, Self-Holding,		1	pc	
		Screwdriver Shaft 1.52.0 Cruciform,self -holding		1	pc	
		Screwdriver Shaft, Hexagonal small, ø 2.5 mm		1	pc	
		Screwdriver Shaft, Hexagonal for screws ø 1.5 mm and 2.0 mm		1	pc	
		Vario Case ™ Framing with Bottom, Size 1/2, height 88 mm		1	pc	
		Lid (stainless stel), Size 1/2, for Vario Case		1	pc	
		Extraction Module for screw ø 3.5, 4.0 and 4.5 mm		1	Unit	
		Which consists of:				
		Screwdriver Shaft 1.0, T25, Length 100mm		1	pc	
		Hollow Reamer, Complete, anticlockwise cutting, for screws ø 3.5 mm and 4.0 mm		1	pc	

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		Hollow Reamer, Complete, anticlockwise cutting, for screws ø 4.5 mm		1	pc	
		Spare Reamer Tube, for No.309.035		1	pc	
		Spare Reamer Tube, for No.309.450		1	pc	
		Extraction Bolt, for screws ø 3.5 mm and 4.0 mm		1	pc	
		Extraction Bolt, for screws ø 4.5 mm and 5.0 mm		1	pc	
		Extraction screw, conical, for screws ø 2.7, 3.5, and 4.0 mm		1	pc	
		Extraction screw for screws ø 3.5 mm		1	pc	
		Extraction screw, conical for screws ø 4.5 mm and 6.5 mm		2	pcs	
		T-Handle with Quick Coupling		1	pc	
		Screwdriver Shaft, hexagonal, small, Ø 2.5 mm		1	pc	
		Screwdriver Shaft Stardrive® 3.5, T15, self-holding, for AO/ASIF Quick Coupling		1	pc	
		Screwdriver Shaft, hexagonal, large, Ø 3.5 mm		1	pc	
		Vario Case™, Framing with Bottom, size 1/2, height 88 mm		1	pc	
		Lid (stainless steel), size 1/2, for Vario Case™		1	pc	
		Extraction Module for Screws Ø 5.0, 6.0, 6.5, 7.0 and 7.3 m		1	Unit	
		Which consists of:				
		Screwdriver Shaft, hexagonal, hexagonal head 4 mm, length 100 mm		1	pc	
		Screwdriver Shaft, T25, length 100 mm		1	pc	
		Screwdriver Shaft, T40, length 100 m		1	pc	
		Screwdriver Shaft, hexagonal, large, Ø 3.5 mm		1	pc	
		Hollow Reamer, Complete, anticlockwise cutting, for Screws Ø 5.0, 6.0, 6.5 and 7.0 mm		1	pc	
		Hollow Reamer, Complete, anticlockwise cutting, for Screws Ø 4.5 mm		1	pc	
		Spare Reamer Tube, for No. 309.065		1	pc	
		Spare Reamer Tube, for No. 309.450		1	pc	
		Extraction Bolt, for Screws Ø 6.0, 6.5 and 7.0 mm		1	pc	

NO.	Item	Purchaser's Specifications	Quantity	Statement of Compliance (Bidder's Offered Item & Specification)
		Extraction Bolt, for Screws Ø 4.5 and 5.0 mm	1 pc	
		Extraction Screw, conical, for Screws Ø 2.7, 3.5 and 4.0 mm	1 pc	
		Extraction Screw for Screws Ø 3.5 mm	1 pc	
		Extraction Screw, conical, for Screws Ø 4.5 and 6.5 mm	2 pcs	
		T-Handle with Quick Coupling	1 pc	
		Vario Case™, Framing with Bottom, size 1/2, height 88 mm	1 pc	
		Lid (stainless steel), size 1/2, for Vario Case™	1 pc	
		HSS Drill Bit		
		HSS Drill Bit Ø 2.5 mm for Implant Steel, sterile	2 pcs	
		HSS Drill Bit Ø 3.5 mm for Implant Steel, sterile	2 pcs	
		HSS Drill Bit Ø 4.8 mm for Implant Steel, sterile	2 pcs	
		CARBIDE Drill Bit		
		Carbide Drill Bit Ø 4.0 mm for Instrument Steel and Titanium, sterile	2 pcs	
		Carbide Drill Bit Ø 6.0 mm for Instrument Steel and Titanium, sterile	2 pcs	
15	PAIN EQUIPMENT (ANAESTHESIA)			
15.1	Radiofrequency		1 Unit	
		OUTPUT STIMULATOR :		
		Frequency Coverage : 2, 5, 50, 75, 100, 150, 180, 200Hz		
		Duration : 0.1, 0.5, 1, 2, 3 milli sec		
		Voltage Stimulation Mode : 0 – 5 volts		
		Constant Flow Stimulation Mode : 0 –10 mA		
		OUTPUT THERMAL & PULSED RF		
		Timer : What can be chosen: 0:30 - 30:00 minutes		
		* Resolution : 1 Second		
		* Accuracy : ± 1%		
		Watt : 0 to 50 watts RMS		
		* Resolution : 1 watt (only on Thermal RF output)		
		* Accuracy : 20% on full scale (only on Thermal RF output)		
		* Frequency : 480 kHz		

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		Volt	: 0 to 70 volts RMS when loading 100Ω during Thermal RF output.			
			: 0 to 100 volts peak at 100Ω during Pulsed RF output.			
		*Resolution	: 1 volt RMS during Thermal RF output			
			: 1 volt peak during Pulsed RF output			
		* Accuracy:	: 10% of full scale			
		Electric Current	: 0 to 700 mA RMS			
		*Resolution	: 1 mA RMS during Thermal RF output			
			: 1 mA peak during Pulsed RF output			
		* Accuracy	: 10% of full scale			
		RF PULSED SETTINGS:				
		Average Repetition	: 1, 2, 3, 4, 5, 6, 7, 8 PPS (Hz)			
		Duration of Series	: 2 - 50 ms			
		MONITOR TEMPERATURE				
		Range	: 0 – 120°C			
		Resolution	: 1 °C			
		Accuracy	: ± 3 °C between 40 and 90 °C			
			: ± 4 °C between 0 and 40 °C, and between 90 and 110 °C			
		OUTPUT TEST				
		The Test Plug output allows temperature testing and impedance measurements, and all RF output from the Output Jacks Generator				
		TOUCH SCREEN				
		Touch screen capability for generator programming and output control functions.				
		OUTPUT DATA				
		Via a USB connection on the back of the panel				
		HANDLING WITHOUT CABLE: CONTROL				
		Cordless Hand Control is available for all generator functions				

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		OTHER SPECIFICATIONS				
		Dimension approx.	:			
		Length 36.2 cm, lwidth 30.9cm, height 24.1 cm				
		weight approx. : 11 kg				
		ELECTRICITY SUPPLY				
		Maximum input voltage	: 260 Volt AC			
		Maximum voltage at input connector	: 260 Volt AC			
		Maximum input power	: 480 VA			
		Supply Current	: 2.0 Amp ~ alternating sinusoidal wave current			
		Fuses	: 2.0 Amp (T) time-lag			
		Frequency	: 50/60 Hz			
		OPERATIONAL ENVIRONMENT RANGE				
		Temperature	: 15 - 40 ° C			
		Humidity	: 15 - 80% non-condensing relative humidity			
		Atmospheric Pressure	: 500 - 1060 hPa			
		MONITOR IMPEDANCE				
		Range	: 0 - 3000 ohms digital			
		Resolution	: 1 ohm between 0 - 999, 100 ohms between 1000 - 3000			
		Accuracy	: 10 ohms between 20 and 50 ohms 20% between 51 and 3000 ohms			
16	COSMETIC EQUIPMENT					
16.1	Centrifuge PRP			1	Unit	
		Max. Speed	: 0-4000rpm (Fixed) Max. RCF : 1795 x g			
		Capacity	: 6,8,12 x 15 ml angle rotor			
		Timer	: -120 min			
		Power supply	: AC 220v 50Hz approx 40w			
		Dimension approx	: L280 x W240 x H260 mm			
16.2	Nano FRX			1	Unit	
		Type	: RF			
			: EP: RF : Yes			
		Style	: Portable Certification: KFDA			
		Feature	: Face lift, Skin rejuvenation, weight loss, Wrinkle Remover			
		Aplication				
			Wrinkes removal			
			Acne scars removal			
			Deep and shallow scars removal			

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
			Tightening			
			Lifting			
			Contouring			
			Large pores shrink			
16.3	Derma pen			1	Unit	
		Type	: Electroportation and microneedling			
		Needling RPM 1				
		Level	: 4000 2 level 4,500, 3 Level 5000			
		Depth of needle	: 0-2mm.			
		Needle Gage	: 33G			
		Electroportation	: 5 intensity levels			
		Needle:	: disposable sterilized needle			
16.4	Oxybubble			1	Unit	
		Input voltag	: 100-200 V, 50-60 Hz, 0,7-0,45 A			
		Apparent power	: 30W approx			
		Power consumption	: 28W approx			
		Display	: 7"LCD Monitor			
		Input	: Touch Screen Weight: 2.5kg approx			
		Size approx.	: 210(w)180(L)x255(H) mm			
17.	Fertility CENTER					
17.1	Hepa Filter System			1	Set	
		Interior Material				
		Wall Panel & installation material	Medical Insulated Panel 50 mm	113	m2	
		Ceilling Panel & installation material	Medical Insulated Panel 50 mm	53	m2	
		Manual Double Swing	Manual Double Swing Door			
		Door	2 x 800 x 2100 x 50 mm approx.	2	sets	
		Manual Single Swing	Manual Single Swing Door			
		Door	900 x 2100 x 50 mm approx	1	set	
		Automatic Single	Automatic Single Sliding Door			
		Sliding Door	1100 x 2100 x 50 mm approx	1	set	
		Equipment				
		- Pass box	2 doors with glass, 660 x 450 x 560 mm approx	1	unit	
		- Lighting Standard	3x16 W LED-32W.220V,			
		Wiring Cable & Work	c/w COVER ACRYLIC.	4	units	
		- Lighting with Dimmer	3x16 W LED-32W.220V,			
		Wiring Cable & Work	c/w COVER ACRYLIC.	2	units	
		- Power Source Unit	Universal Socket x 4, Grounding			
		Wiring Cable & Work	Terminal x 2	7	sets	
		- Power Panel				

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
	Medical Gas Unit					
	- Medical Gas Panel	R. Embriology, R. Opu, R. Insemination	1	unit		
	Wall Point Outlet O, N, CO2	R. Preparation				
	Clean Room Unit					
	- AHU DX 100.000 BTU	Positive pressure 30 kpa class 10000	1			
	- AHU DX 80.000 BTU	Positive pressure 20 kpa class 10000	1			
	- Ducting	Polyurethane	162	m2		
	- Diffuser	approx 40 x 40 cm	8	pcs		
	- Grille	approx 60 x 30 cm	9	pcs		
	- Cover	approx 25 x 20 cm	2	pcs		
17.2	CodaAir 800 - A 800-008 + Filter		2	Units		
	24V Universal Adapter					
	Coverage : 46 - 65 m2					
	Air exch. per hour : 4 – 22 times					
	Weight : 24 kg approx					
	Size : d x w x h	30 x 46 x 66 cm approx.				
	Shirt Box filter system					
	2" pleated filter					
	2" carbon/potassium filter					
	4" HEPA					
	HEPA 99.97%					
	Carbon & potassium permanganate mix					
	Kilograms : 2 approx					
	Initial filter included with purchase					
	Semi-annual filter (change every 6 months)					
	Cat.#s : GCAF-702 (2 filters)					
17.3	Stereo Microscope		1	Unit		
	- Optical system: Parallel-optics zoom system					
	- Total magnification: 5 – 480x (depending on eyepiece and objectives)					
	- Interpupillary distance adjustment: 48-75 mm					
	- Zooming range: 1x to 8x (with 1/2/3/4/5/6/7/8x stops)					
	- Zooming ratio: 8 :1					

NO.	Item	Purchaser's Specifications	Quantity		Statement of Compliance (Bidder's Offered Item & Specification)	
17.4		- Working Distance: 78mm (with Plan 1x)				
		- Focusing: fine Focusing knob included				
		- Total Magnification being used: 10-80x				
		Consisting of:				
		SMZ800N Zooming Body				
		C-W10XB Eyepiece 10X (2pcs)				
		P-B Binocular Tube				
		P-PLAN 1X (W.D. 78 mm)				
		C-FMCN Focusing Mount C with coaxial coarse & fine focusing knobs				
		P-IBSS2 Beam Splitter S2				
		LV-TV Tube for TI3				
		C-Mount TV Adapter A				
		Cover Type 104				
		P-IBSS2 Beam Splitter S2				
		LV-TV Tube for TI3				
		C-Mount TV Adapter A				
		Cover Type 104				
		Air Incubator		1	Unit	
		- Capacity	233 litres			
		- Internal dimension (W/H/D) :	approx. 610x672x570 mm			
		- External dimension (W/H/D) :	approx. 754x910x570 mm			
		- Number of shelves :	2			
		- Perforated shelves : C1862	max. 16			
	- Shelf dimension (W/D) :	558x530				
	- Max. load :	approx. 70kg				
	- Weight :	approx. 75kg				
	- Operating temperature :	50° C to 70° C				
	- Temperature deviation at 37° C :	> 1° c				
	- Heat transfer to environment (at 37° C) :	40Wh/h				
	- Operating voltage :	230 V				
	- Frequency :	50-60Hz				
	- Power consumption :	approx. 0,57 kW				
17.5	Micro pipettor (The Stripper)		2	Units		
	- Gamma irradiated for sterility					
	- Endotoxin tested					
	- Mouse embryo tested					
	- Flexible, Unbreakable					

NO.	Item	Purchaser's Specifications	Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		- Volume max. : 500 µl			
17.6	Micro pipettor (The Stripper CC)		2	Units	
		OOCYTE/EMBRYO HANDLING TOOL FOR TRANSFER OF CUMULUS COMPLEX DURING RETRIEVAL			
17.7	Incubator Analyzer for Measuring CO2, O2, RH + Accessories		1	Unit	
		- Weight : 750 g			
		- Storage temperature : -40°C to +70°C			
		- Storage humidity : 0-100% RH Non considering			
		- Materials : ABS/PC blend			
		- Pressure : 0-20 bar			
		- Power consumption : Rechargeable NIMH battery pack with AC power or 4 AA alkaline batteries type IEC LR6			
		- Analog output : 0-1 VDC			
17.8	IVF Thermometer + Spare Probe		1	Unit	
		- Calibrated at IVF temperature			
		- with IVF micro-probe			
		- Waterproof case			
		- Digital display			
		- Sensor type : T			
		- Connector type : Lumberg			
		- 3 pre-set calibration points : 5°C, 37°C, 45°C			
		- Accuracy : ± 0,2°C			
		- Range : -250°C to +400°C			
		- Response : Fast			
17.9	Individual Benchtop CO2 Incubator		1	Unit	
		Contamination Free			
		Culturing with no humidity provides no risk for contamination in the embryo-culturing environment.			
		Individual Control			
		6 separate chambers provide an optimal environment for embryo development.			

NO.	Item	Purchaser's Specifications	Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		Fast recovery for the gas concentrations and the temperature.			
		Dependable alarm systems for temperature, gas concentrations and gas flow			
		External dimensions : 517.5 x 608 x 171 mm (W x D x H) approx.			
		Chamber dimensions : approx. W108xD180xH18.5 / chamber			
		Chamber capacity : 300 ml (with bottom plate attached)			
		Chamber warming plate : 6 plates standard			
		Chamber gas flow sensor : Installed in each chamber			
		Temperature Control : Digital PID Control			
		Temperature Range : Ambient +5~40 Celcius			
		Temperature Accuracy : ±0.1 Celcius			
		CO2 Sensor : Infra Red Sensor			
		CO2 Control : Duty Control			
		CO2 Range : 0~20.0%			
		CO2 Accuracy ±0.3%			
		O2 sensor : Ceramic oxygen sensor			
		O2 Control : Duty Control			
		O2 Range : 0.1~18.0%			
		O2 Accuracy : ±0.3%			
		Gas Requirement 100% CO2 and N2			
		Alarms Temperature upper limit, Gas deviations (CO2/O2), gas flow, gas pump			
		Option : Can be connected to a PC incubator monitor system			
		Monitoring with dedicated EZC-Logger software			
		Weight : approx. 26 kg			
		POWER AC : 100V/110V/220V			
17.10	Laminar Air Flow Cabinet (LAF) + Accessories		1	Unit	
		- Dimension : 1,000(W) x 1,170(H) x 810(D) mm			approx.
		- Work area : 920(W) x 645(H) x 585(D) mm			approx.
		- Equipment weight : approx. 110kg			

NO.	Item	Purchaser's Specifications	Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		- Max. load capacity of work surface: 30kg	approx.		
		Filter technology			
		- Supply/exhaust air filter type: HEPA H 14 EN 1822, 99.999% at 0.3 µm particle size			
		- Additional Exhaust Filter (AEF) type: HEPA H 14 EN 1822, 99.999% at 0.3 µm particle size			
		- Prefilter: Type (EN 779), G 3 dust filter, filtering efficiency: coarse – medium			
		- Air velocity : 0.45 ± 20% (reduced flow = 0.23 ± 20%)			
		Performance			
		- Lighting intensity: > 1000 lux			
		- Noise pressure level: < 55 dB(A)			
		- This clean bench use less energy to operate by using DC motor			
		- Protection Class : I / IP-20			
		- Standards: EN 61010-1:2011, EN 61326: 2006			
		- Min. clearance from room ceiling: 150mm			
		- Side windows: tempered safety glass			
		- Table top: white melamine			
		- Receptacles: 3			
		Optional:			
		Fixed height floor stand 0.9m. Provides work height of 760 mm			
17.11	Hepa Portable Aero 500 - GCAU-000 + Filter or Similar		2	Units	
		Coverage : 28-55 m2			
		Air exch. per hour : 8-14 times			
		Weight : 20.41 kg	approx.		
		Change filters every 3 months			
		Initial filter kit : included			
		Quarterly kit : GCAF – 001 (1pk)			
		GCAF – 002 (1 pk)			
17.12	Binocular Microscope	Olympus Trinocular Microscope Model CX33TRINO-BF standard set,	or similar		
		with specification:			
		Optical System Illumination : Infinity optical system			

NO.	Item	Purchaser's Specifications	Quantity	Statement of Compliance (Bidder's Offered Item & Specification)
		System : Built-in transmitted illumination system, Kohler		
		illumination (fixed field diaphragm), LED power		
		consumption 2.4 W (nominal value), precentered		
		Focusing :		
		•Stage height movement (coarse movement stroke: 15mm)		
		•Stroke per rotation: 36.8mm, focusing stopper		
		•Torque adjustment for coarse adjustment knob		
		•Fine focus knob (minimum adjustment gradations: 2.5µm)		
		Nosepiece : Revolving fixed quadruple nosepiece with inward tilt		
		Observation tube		
		Type : Trinocular with a pair of eyepieces 10x		
		Field number : 20		
		Tube inclination: 30		
		Interpupillary distance : 48 – 75 mm		
		adjustment range		
		Light path selector : none		
		Stage		
		Size : 211 (W) x 154 (D) mm	approx.	
		Movement range : 76mm X-direction x 52mm Y-direction		
		Specimen Holder : Single specimen		
		Condenser		
		Type : Abbe condenser		
		N.A : 1.25 with oil Immersion		
		Aperture iris diaphragm : Built-in		
		Observation method : Brightfield		
		Dimension / weight 211 (W) x 430 (H) x 397 (D) mm / approx. 7 kg		
		Objective lens : - Plan Achromatic 4X, NA: 0.10, WD: 27.8 mm (antifungus)		
		- Plan Achromatic 10X, NA: 0.25, WD: 8 mm (antifungus)		
		- Plan Achromatic 40X, NA: 0.65, WD: 0.6 mm (antifungus)		
		- Plan Achromatic 100X, NA: 1.25, WD: 0.13 mm		

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
17.13		(spring,oil)				
		- Dust cover, Power Cord, immersion oil				
	Centrifuge			1	Unit	
		- Routine clinical and life science applications, with a 2-in-1 hybrid rotor				
		- Four customizable programs to quickly run routine protocols				
		- DualSpin rotor features hybrid design with interchangeable fixed angle and 'swinging buckets'				
		- Emergency lid lock release available in case of power failure				
		- Quiet operation at noise level less than 56 dBA				
		- Lightweight composite rotor is easy to handle and saves energy during acceleration/deceleration				
		- Conforms to the latest clinical and safety standards, such as UL, CE and IVD1				
		Maximum Capacity : 8 x 15 mL (fixed angle)				
		8 x 10 mL (swinging bucket)				
		Maximum Speed : 300-4,900 rpm, adjustable in increments of 100 rpm				
		Maximum RCF : 3,114 x g (fixed angle)				
		3,490 x g (swinging bucket)				
		Time Setting : 1-99 minutes, in increments of 1 minute; HOLD				
		Temperature Range : 2°C to 40°C				
		Control System : Microprocessor				
		Program Memory : 4				
		Acceleration Profile : 1 (standard)				
		Deceleration Profiles : 3 (standard, soft, brake-off)				
	Power Consumption : 100-130 W, voltage dependent					
	Dimensions (H x W x D) :240 x 325 x 450 mm	approx.				
	Weight : 15.5 kg	approx.				
	Standards : IEC 61010-1, IEC 61010-2-020, IEC 61010-2-101, EN 61326-1, EN ISO 13485					

NO.	Item	Purchaser's Specifications	Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
17.14	Laboratory Refrigerator		2	Units	
		External dimensions :			
		W540 mm x D557 mm + (45)* mm x H1794 mm approx.			
		Internal dimensions :			
		W455 mm x D466 mm x H917 mm <Refrigerator> approx.			
		W420 mm x D342 mm x H267 mm <Freezer> approx.			
		Effective capacity : 176 L (Refrigerator), 39 L (Freezer) approx.			
		Exterior : Painted steel			
		Interior : Styrene resin (Refrigerator), colored aluminum (Freezer)			
		Door : Painted steel, provided with glass window (Refrigerator)			
		Insulation : Rigid polyurethane foamed-in place			
		Refrigerator : Hard steel wire on polyethylene coating x 5, Allowable load; 20 kg/shelf; Inner dimensions; W388 mm x D325 mm			
		Freezer : Hard steel wire on polyethylene coating x 1, Allowable load; 10 kg/shelf; Inner dimensions; W327 mm x D250 mm			
		Access port : Inner diameter; 30 mm, Left side (refrigerator and freezer)			
		Cooling method : Forced air circulation (refrigerator), Direct cooling (freezer)			
		Compressor : Hermetic reciprocating type, Output; 55 W x 2			
		Evaporator : Fin and tube type (refrigerator), Tube on sheet type (Freezer)			
		Condenser : Wire and tube (Refrigerator), Frame pipe (Freezer)			
		Refrigerant : R-134a			
		Defrosting : Cycle defrost and forced defrost (refrigerator)			
		Natural defrost by stopping operation (Freezer)			
		Defrost heater : 46.3 W (refrigerator)			

NO.	Item	Purchaser's Specifications	Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		Temperature controller : Electronic control system			
		Temperature display : Digital display (in 1°C increments)			
		Thermal sensor : Thermistor sensor			
		Alarms : High temp. alarm, Low temp. alarm, 0°C alarm (refrigerator only), Door alarm, Power failure alarm (remote alarm only)			
		Safety functions : Over-heat protection (refrigerator only), Over-cool protection (refrigerator only), Key lock, Auto-return			
		Self diagnostic : Thermal sensor abnormality, Fan motor check			
		Memory backup : Nonvolatile memory			
		Lamp : Incandescent lamp (T22 E17) 110 V or 125 V, 10 W x 1 (refrigerator)			
		Weight : 86kg		approx.	
		Accessories : 1 set of key, 2 large clips (for temperature recorder)			
		Optional components :			
		Temperature recorder for refrigerator (MTR-0621LH)			
		Temperature recorder for freezer (MTR-4015LH),			
		Recorder fixing for MTR-4015LH (MPR-S30),			
		Temperature recorder for refrigerator & freezer (MTR-G3504A or MTR-G3504C),			
		Recorder fixing for MTR-G3504 or MTR-G3504C(MPR-S7)			
		Data acquisition system (MTR-5000)			
		Interface board (MTR-480, MTR-L03)			
		Temperature control range :			
		Refrigerator: between 2 and 14°C (ambient temp.; -5 to 30°C, no load)			
		Freezer: between -20 and -30°C (ambient temp.; -5 to 30°C, no load)			
		Noise level : 35/36 dB (A scale) (50 Hz/60 Hz)			
		Maximum pressure : 1900kPa			

NO.	Item	Purchaser's Specifications	Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		Rated voltage : AC 220 V/230 V/240 V			
		Rated frequency : 50Hz			
		Power consumption : 155 W approx.			
		Usable condition : -5 to 30°C, 80%R.H. or less			
17.15	Pipette Filler		1	Unit	
		Volume Range : 1 mL – 10 mL			
		Increment (electric) : 10 µL			
		Accuracy ± : 1 mL : 5 % / 50 µL ; 5 mL : 1 % / 50 µL ; 10 mL : 0.6 % / 60 µL			
		Precision ± : 1 mL : 0.6 % / 6 µL ; 5 mL : 0.2 % / 10 µL ; 10 mL : 0.16 % / 16 µL			
		Tip Technology : LiteTouch System LTS			
		Channels : 1			
		Maximum Volume : 10 mL			
17.16	Pipettor 10-100 ml		2	Units	
		- Single channel manual pipette			
		- Pipette research adj. volume 10-100 µl			
17.17	Pipettor 20-100 ml		2	Units	
		- Single channel manual pipette			
		- Pipette research adj. volume 20-100 µl			
17.18	Pipettor 100-1000 ml		2	Units	
		- Single channel manual pipette			
		- Pipette research adj. volume 100-1000 µl			
17.19	USG 2 D + Probe Transvaginal & Abdominal		2	Units	
		Physical Appearance			
		Screen Display : 17" TFT LCD			
		Weight : 65 Kg			
		USB Port : 5			
		HDMI Out : Yes			
		Probe Port : 3			
		Keyboard : Yes			
		Basic Software			
		Raw Data : Yes			
		M-Mode : Yes			
		2D Mode : Yes			
		Power Doppler : Yes			

NO.	Item	Purchaser's Specifications	Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		PW Doppler	: Yes		
		Optimization Tools	: Yes		
		Advance Software			
		SonoBiometry	: Yes		
		Biopsy Kit	: Optional		
		Probes Included			
		Convex	: Yes		
		Transvaginal	: Yes		
		Connectivity			
		Image Format	: JPEG, BMP, TIFF		
		Video Format	: AVI, MOV		
		DICOM Format	: Yes		
		USB Port	: 4		
		LAN Port	: Yes		
		Workstation	: Optional		
		Peripherals			
		B/W Printer	: Yes, included		
		Color Printer	: Optional		
		CD/DVD Writer	: Yes, included		
		UPS	: Optional		
17.20	Patient Monitor			2 Units	
		Size	10.4 inch		
		Type	Active matrix color TFT LCD		
		Resolution	SVGA (800 x 600)		
		Number of traces	Up to 6		
		Number of digit fields	Up to 4		
		Display layout and colors	User-configurable		
		Weight	approx. 6 Kg		
		ComWheel, function keys and menu keys			
		Frame			
		Extension Module	Mini - C (optional)		
		I/O connections	RS-232 computer serial output, Defibrillation synch, ECG and IBP analog outputs, Nurse call.		
		Network	Compatible with S/5 Network and iCentral for centralized viewing and remote alarm management		
		Trends			
		Graphical	All parameters, selectable times from 20 minutes to 72 hours.		

NO.	Item	Purchaser's Specifications	Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
	Numerical	All parameters, sampled every 5 min after NIBP measurement and			
		with marker generated by user			
	Trend cursor	In both graphical and numerical trends			
	Minitrends	5 or 30 minute minitrends can be displayed for a continuous historical view			
	Alarms				
	Classification	Alarm system classified into three categories according to priority in critical care ; color and audio tone coded			
	Adjustment	Central alarm display and adjustment page			
	Trending	10 min graphical minitrends referenced to set alarm limits.			
	Power				
	Power requirement	100 to 240V ±10%, 50/60 Hz			
	Protection class	Class I			
	Battery				
	Type	Exchangeable lithium-Ion, 2 pcs (max.)			
	Operation time	Up to 4.5 hours			
	Environmental specifications				
	Temperature				
	Normal	5°C to 40°C (41°F to 104°F)			
	Charging batteries	5°C to 35°C (41°F to 95°F)			
	Relative humidity	20% to 90% non-condensing			
	Certifications				
	IEC 60601 - 1 passed				
	CE marking according to Directive 93/42/EEC				
	Technical data (Module)				
	ECG				
	Lead type	3-lead (I, II, III)			
		5-lead (I, II, III, aVL, aVF, aVR, V) - Optional Cable Needed			
	Sweep speed	12.5, 25 or 50 mm/s			
	Gain range	0.2 to 5.0 cm/mV			
	Heart rate range	30 to 300 bpm			
	Filter	Monitor : 0.5 to 30/40 Hz ST			
		0.05 to 30/40 Hz Diagnostic			
		0.05 to 150 Hz (50/60 Hz power supply, 3 dB)			
	Defibrillation	5000 V, 360 J			
	Pacemaker				
	Range	2 to 700 mV			
	Pulse width	0.5 to 2 ms			

NO.	Item	Purchaser's Specifications		Quantity	Statement of Compliance (Bidder's Offered Item & Specification)
	Arrhythmia analysis	Ek-Pro arrhythmia analysis			
	ST segment analysis				
	Display resolution	-9 to +9 mm (-0.9 to +0.9 mV)			
	ST segment range	0.1 mm (0.01 mV)			
	ST trends	Up to 72 hours			
	Respiration				
	Method	Transthoracic impedance			
	Respiration range	4 to 120 resp/min			
	Accuracy	±5% or ±5 breath/min			
		whichever is greater			
	Sweep speed	Slow 0.62 mm/s, fast 6.25 mm/s			
	Gain range	0.1 to 5 cm/ohm			
	NIBP				
	Display parameters	Systolic, diastolic and mean arterial pressure			
	Operation mode				
	Measurement principle	Manual, Auto, STAT			
	Measurement range	SuperSTAT, Oscillometric with step deflation			
		Systolic			
		Adult/Paediatric 30 to 290 mmHg			
		Neonate 30 to 140 mmHg			
		MAP			
		Adult/Paediatric 20 to 260 mmHg			
		Neonate 20 to 125 mmHg			
		Diastolic			
		Adult/Paediatric 10 to 220 mmHg			
		Neonate 10 to 110 mmHg			
	Default initial inflation pressure	Adult/Paediatric 135 ± 15 mmHg			
		Neonate 100 ± 15 mmHg			
	Maximum Determination Time	Adult/Paediatric 2 minutes			
		Neonate: 85 seconds			
	Over Pressure Monitor	Adult/Paediatric: 300 to 330 mmHg			
		Neonate: 150 to 165 mmHg			
	Accuracy	Meets AAMI SP10			
	SpO2				
	Technology	GE Datex-Ohmeda			
	Measurement accuracy	0 to 100%			
	Display range	100 to 70%, ±2 digits,			
		±3 digits during clinical patient motion ;			
		69 to 0%, unspecified			
	Display resolution	1 digit (1% of SpO2)			
	Pulse rate				
	Display range	30 to 250 bpm			
	Display resolution	1 digit (1 bpm)			

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
17.21		Accuracy	±5% or ±5 bpm			
	Test Tube Heater + Power Supply			1	Unit	
		Test tube heater	: G18226 KFTH-1012			
		Alternative Power Supply	: For use with test tube heater (K-FTH1012) : G49337 K-APS-300			
17.22	Electric Gynaecological Table			3	Units	
		Construction	: Electric Actuator for Back Raise and Hi-Lo adjustment			
		Dimension	: 1940mm (L) x 610mm (W), Low Position 640mm, High Position 1080mm			
		Steel finishing	: Epoxy Powder Coating			
		Bed construction	: Steel Pipe & Steel Plate			
		Back raise	: Adjustable by remote			
		Hi-Lo position	: Adjustable by remote			
		Mattress	: Foam with laminated leather			
		Castor	: 2"			
		Leg support	: Waste collection basin			
		Waste collection basin	: Moveable			
17.23	Anaesthesia Machine			1	Unit	
		Main Unit	TV setting 20-1500ml, including: 10.4 inch touch color screen, ventilator, glass flowmeters (hypoxic guard), work surface, 2 drawers, 1 battery (90 min), 20 pcs of foam pad, pipeline pressure gauges, user manual, quick user guide, packing material			
		PCV	Pressure controlled ventilation mode (PCV)			
		O2 Sensor	O2 monitor and accessory kit, including: -O2 sensor, Medical MOX-2, 1 pc -O2 sensor cable			
		Independent ACGO	Independent ACGO for EX-20\30\35 with pressure monitoring			
		Software Language	English version			
		Power Cord	Power cord (Europe)			
		Machine ID	European (ID) style			
		Pipeline (Hose) inlet	NIST-2 (European)			
	Gas supply	O2 & N2O & Air (glass flowmeter for 20/30/35)				

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)
		Gas hose	O2 & N2O & Air hoses			
		Driven gas	O2 drive			
		Vap position	2 vaporizer position (Selectatec)			
		Breathing circuit	PSU Breathing circuit (w/arm, w/heating system, w/o CO2 bypass)			
		AGSS	Active AGSS system or Passive AGSS system			
		SIMV	SIMV mode (SIMV-VC and SIMV-PC)			
		PSV	Pressure supported ventilation mode (PS, w/ apnea backup)			
		One Vap	V60 Sevoflurane vaporizer (Quick-fill)			
		Additional Vap	V60 Isoflurane vaporizer (Pour-fill)			
		Auxiliary O2 outlet	Auxiliary O2 flowmeter			
		Power Outlet	Auxiliary sockets			
		Accessory	Reusable accessory kit (Adult)			
			Reusable accessory kit (Child)			
			Demo lung (Test lung) for adult			
			breathing bag,silicon 0.5L			
			breath bag,silicon 2L			
			T-Piece System type (Children open circuit)			
			Bacteria Filter			
17.24	Scrub Station			1	Unit	
		- Overall Length	: 1600 mm approx			
		- Overall Width	: 600 mm approx			
		- Overall Height	: 1500 mm approx			
		- The basin frame adopted high quality 1.0mm thick 304 stainless steel				
		- The design of the tank has greatly prevented splashing				
		- The basin adopted two automatic induction tap, induction distance of the				
		- The basin equipped with two automatic induction tap, water comes out				
		- The water comes out automatically while people walk into induction sector, which efficiently avoid bacterial mutual infections				
		- Automatic induction hand cleaner supplier, supplies 3-5ml each time				
		- Place hands below the supplier 10-15cm				
		- Energy saving design, the longest time supply water is 5 minutes, the				
		- The water pipe adopted steel woven pipe, heat-resistant and anti-aging				
		- The whole basin adopted bending, greatly deduced welding, it's hard-warring and easy to clean				
		- The temperature of water is adjustable				
		Working Condition :				
		- Voltage : AC220V ~ 250 V				
		- Frequency : 50Hz ± 1 Hz				
		Standard Accessories				

NO.	Item	Purchaser's Specifications		Quantity		Statement of Compliance (Bidder's Offered Item & Specification)	
17.25		- Two set of automatic induction tap					
		- One set of automatic induction hand cleaner supplier					
		- One set of 40 L water heater					
		- All electrical appliance of the basin, fully equipped with protection device of leakage, lack of water and detention on water supply					
		LED Examination Lamp, Mobile			3	Unit	
		LED (standard)	Approx. 18.000 Lux				
		Power Supply	AC 220 V , 50 Hz, 50 Watt				
		Adjustable stand	Stainless steel or aluminium casting alloy				
		Base	5 foot				
	Castors	5 castors Ø 10 cm					
	Dimension	approx diam. 60 cm x120-170cm hight with flex arm					
	Weight	approx. 12 kg					